



Heavy Duty Toggle Switches - 3 Pole



- Motor Control & Tool Applications
- Solid Brass or Nickel Plated Bushings
- 1/2" Mounting Hole
- Dielectric Strength: 1500V
- Mechanical Life Cycles: 100,000
- 32°F to 185°F

CAT. NO.	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	STANDARD LOAD RATING	MOTORLOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
70301	3PST	ON-OFF	SCREW	6	18A 125VAC 10A 250VAC	18A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.32 X 1.09 X 1.11	1	10
70302	3PDT	ON-ON	SCREW	9	18A 125VAC 10A 250VAC	18A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.32 X 1.09 X 1.11	1	10
70303	3PDT	ON-OFF-ON	SCREW	9	18A 125VAC 10A 250VAC	18A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.32 X 1.09 X 1.11	1	10

Heavy Duty Toggle Switches - 4 Pole



CAT. NO.	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	STANDARD LOAD RATING	MOTORLOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
70304	4PST	ON-OFF	SCREW	8	16A 125VAC 10A 250VAC	16A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.43 X 1.40 X 1.07	1	10
70305	4PDT	ON-ON	SCREW	12	16A 125VAC 10A 250VAC	16A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.43 X 1.40 X 1.07	1	10
70306	4PDT	ON-OFF-ON	SCREW	12	16A 125VAC 10A 250VAC	16A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.43 X 1.40 X 1.07	1	10

Medium Duty Toggle Switches

- 1/2" Mounting Hole
- Dielectric Strength: 1500V
- Insulation Resistance: 500V



CAT. NO.	TYPE	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	LOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
70050	TOGGLE WITH ON/OFF FACEPLATE WIRE LEAD	SPST	ON-OFF	6" WIRE LEADS	N/A	8A 125VAC 4A 250VAC 1/3HP 125V	.98 X .62 X .62	1	10
70060	TOGGLE WITH ON/OFF FACEPLATE	SPST	ON-OFF	SCREWS	2	6A 125VAC 3A 240VAC	.69 X .57 X .40	1	10
70062	TOGGLE SWITCH	SPST	ON-OFF	QUICK CONNECT SPADE	1	21A 12VDC	.69 X .55 X .45	1	10
70061	SHORT BALL BAT TOGGLE SWITCH WITH ON/OFF PLATE	SPST	ON-OFF	6" WIRE LEADS	N/A	6A 125VAC 3A 250VAC	.69 X .55 X .34	1	10