LISTED

COLOR & WATTAGE SELECTABLE
NEW CONSTRUCTION DOWNLIGHTS

CAT. NO.	PRIOR CAT. NO.	TRIM STYLE	SIZE	COLOR TEMP	WATTS	VOLTS	LUMENS @ MAX WATTS	CRI	DIMMING	REPLACES INCANDESCENT	CASE QTY
72769	-	SMOOTH	4"	2700K, 3000K, 3500K, 4000K, 5000K	7W, 10W, 13W	120-277V	1,184	93	0-10V	40-75W	12

DOWNLIGHT WITH JUNCTION BOX

FIG. 1

FIG. 2

FIG. 3

CAT. NO.	FIG.	SIZE	TRIM STYLE	COLOR TEMP	WATTS	LUMENS	VOLTS	CRI	BEAM ANGLE	DIMMING	REPLACES INCANDESCENT	CASE QTY
ROUND DRIVERLESS 120V ONLY												
72676	1	4"	PC BAFFLE	3000K	10W	847	120V	82	101	TRIAC	75W	12
ROUND 120-277V												
72640	1	4"	ALUM BAFFLE	3000K	10W	780	120-277V	92	94	TRIAC @120V	75W	12
72655	2	8"	ALUM BAFFLE	5000K	25W	1,900	120-277V	92	94	TRIAC @120V	150W	6
72686	3	10"	ALUM BAFFLE	4000K	40W	3,592	120-277V	82	98	0-10V	200W	4
72687	3	10"	ALUM BAFFLE	5000K	40W	3,916	120-277V	82	98	0-10V	200W	4
72690	3	10"	ALUM BAFFLE	5000K	50W	4,813	120-277V	82	98	0-10V	300W	4

PLEASE REVIEW ONLINE SPECIFICATION SHEETS. IMAGES AND CERTIFICATIONS MAY NOT BE 100% REPRESENTATIVE OF ALL PRODUCTS LISTED.
TO VIEW DETAILS OF OUR DLC QUALIFIED PRODUCTS, PLEASE CONSULT THE DLC QUALIFIED PRODUCTS LIST AT WWW.DESIGNLIGHTS.ORG/QPL