

Clear Insulated In-line Splices



- Clear Insulation
- 6061-T6 Aluminum
- Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- Pre-filled with Oxide Inhibitor
- Easy Re-Entry for Changes, Inspection or Troubleshooting
- Plugs Marked with Connector Max Wire Size for Easy ID
- CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- One Wire Per Terminal
- Temperature Range of -49°F to 194°F (-45° to 90°C)
- 600 Volt
- UL 486A/486B Listed
- **Indoor Use Only**



CAT. NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS			BOX QTY
			LENGTH	WIDTH	HEIGHT	
97302	2 - 14	SLOTTED/HEX	3.46"	0.82"	1.62"	12
97303	1/0 - 14	3/16"	3.55"	0.96"	2.05"	12
97304	2/0 - 2	3/16"	3.50"	0.99"	1.95"	12
97305	250 - 6	5/16"	4.26"	1.28"	2.28"	4
97306	350 - 6	5/16"	5.21"	1.33"	2.63"	4
97307	500 - 6	5/16"	5.99"	1.84"	3.19"	2
97308	600 - 250	5/16"	6.18"	1.77"	3.17"	2
97309	750 - 250	3/8"	7.39"	1.84"	3.55"	2

Clear Insulated Connectors - Single Side Entry



CAT. NO.	WIRE RANGE	PORTS	ALLEN HEX	DIMENSIONS			BOX QTY
				LENGTH	WIDTH	HEIGHT	
97324	4 - 14	2	SLOTTED/HEX	1.13"	1.10"	1.38"	12
97450	4 - 14	3	SLOTTED/HEX	1.50"	1.10"	1.45"	12
97451	4 - 14	4	SLOTTED/HEX	1.92"	1.10"	1.45"	12
97326	2 - 14	2	SLOTTED/HEX	1.15"	1.20"	1.42"	12
97458	2 - 14	3	SLOTTED/HEX	1.60"	1.20"	1.50"	12
97459	2 - 14	4	SLOTTED/HEX	2.02"	1.20"	1.50"	12
97328	1/0 - 2	2	3/16"	1.69"	1.80"	1.93"	10
97465	1/0 - 2	3	3/16"	1.90"	1.80"	1.93"	10
97466	1/0 - 2	4	3/16"	2.49"	1.80"	1.93"	10
97330	2/0 - 6	2	3/16"	1.69"	1.80"	1.93"	10
97473	2/0 - 6	3	3/16"	1.90"	1.80"	1.93"	10
97474	2/0 - 6	4	3/16"	2.49"	1.80"	1.93"	10
97331	3/0 - 6	2	1/4"	2.00"	1.90"	1.99"	6

CAT. NO.	WIRE RANGE	PORTS	ALLEN HEX	DIMENSIONS			BOX QTY
				LENGTH	WIDTH	HEIGHT	
97481	3/0 - 6	3	1/4"	2.10"	1.90"	1.99"	6
97482	3/0 - 6	4	1/4"	2.87"	1.90"	1.99"	6
97488	250 - 6	3	5/16"	2.40"	2.48"	2.37"	6
97489	250 - 6	4	5/16"	3.29"	2.48"	2.37"	4
97495	350 - 6	3	5/16"	2.80"	2.67"	2.64"	4
97496	350 - 6	4	5/16"	3.85"	2.67"	2.64"	4
97502	500 - 6	3	5/16"	3.18"	2.70"	2.85"	4
97503	500 - 6	4	5/16"	4.35"	2.70"	2.85"	4
97506	600 - 250	3	5/16"	3.40"	2.95"	2.85"	4
97507	600 - 250	4	5/16"	4.68"	2.95"	2.85"	4
97510	750 - 250	3	3/8"	3.60"	3.44"	3.52"	4
97511	750 - 250	4	3/8"	5.03"	3.44"	3.52"	4

Insulated Connectors CONNECTORS