


Copper Split Bolt Connectors - Direct Burial




Copper Split Bolts CONNECTORS



- UL listed for Copper and Copper Weld Stranded Wires Only
- Manufactured from Copper
- Highly Resistant to Cracking and Corrosion
- UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Rated 600 Volts

CAT. NO.	AWG	MAX RUN TO MAX TAP	MIN RUN TO MIN TAP	MAX RUN TO MIN TAP	MIN EQUAL TAP & RUN	TORQUE IN-LB	DIMENSIONS					BOX QTY	
							B	C	L	R	V		W
90314	8	8 - 8	10 - 16	8 - 16	10 - 10	88	0.472"	0.562"	0.854"	0.413"	0.145"	0.650"	100
90316	6	4 - 4	8 - 14	4 - 14	8 - 8	165	0.492"	0.625"	0.906"	0.413"	0.165"	0.722"	100
90318	4	4 - 4	6 - 14	4 - 14	8 - 8	165	0.709"	0.812"	1.16"	0.579"	0.268"	0.938"	50
90320	2	2 - 2	6 - 14	2 - 14	6 - 6	275	0.748"	0.812"	1.26"	0.614"	0.326"	0.938"	50
90322	1/0	1/0 - 1/0	2 - 14	1/0 - 14	4 - 4	385	0.787"	0.937"	1.54"	0.708"	0.374"	1.08"	50
90324	2/0	2/0 - 2/0	1 - 14	2/0 - 14	2 - 2	385	0.866"	1.06"	1.69"	0.807"	0.421"	1.28"	25
90326	3/0	3/0 - 3/0	2/0 - 8	3/0 - 8	1 - 1	500	1.10"	1.25"	2.09"	0.976"	0.531"	1.45"	25
90328	4/0 - 250	250 - 250	4/0 - 8	250 - 8	1 - 1	500	1.10"	1.25"	2.09"	1.06"	0.579"	1.45"	25
90330	350	350 - 350	350 - 1/0	350 - 1/0	2/0 - 2/0	650	1.22"	1.50"	2.36"	1.18"	0.700"	1.73"	12
90332	500	500 - 500	500 - 2/0	500 - 2/0	300 - 300	825	1.34"	1.75"	2.84"	1.34"	0.815"	2.10"	12
90334	750	750 - 750	750 - 350	750 - #8	350 - 350	1000	1.94"	2.31"	3.51"	1.94"	1.02"	2.31"	1

Copper Split Bolt Connectors - With Spacer - Direct Burial



- UL listed for Copper and Copper Weld Stranded Wires Only
- Manufactured from Copper
- Electro Tin Plated
- Spacer Separates Dissimilar Conductors and Provides Enhanced Surface Contact Area Preventing Intermittent Contact Between Run & Tap Connectors
- Free Turning Threads and Easy To Grip Wrench Flats
- Highly Resistant to Cracking and Corrosion
- UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Rated for 600 Volts

CAT. NO.	AWG	MAX RUN TO MAX TAP	MIN RUN TO MIN TAP	MAX RUN TO MIN TAP	MIN EQUAL TAP & RUN	TORQUE IN-LB	DIMENSIONS					BOX QTY		
							B	C	H	L	R		V	W
90360	3/0	3/0 - 3/0	2/0 - 8	3/0 - 8	1 - 1	500	1.10"	1.25"	1.520"	2.20"	0.976"	0.531"	1.45"	25
90362	4/0 - 250	250 - 250	4/0 - 8	250 - 8	1 - 1	500	1.10"	1.25"	1.574"	2.22"	1.06"	0.579"	1.45"	25
90364	350	350 - 350	350 - 1/0	350 - 1/0	2/0 - 2/0	650	1.22"	1.50"	1.771"	2.56"	1.18"	0.700"	1.73"	12
90366	500	500 - 500	500 - 2/0	500 - 2/0	300 - 300	825	1.34"	1.75"	1.968"	2.95"	1.34"	0.815"	2.10"	12