


Aluminum H-Taps



CONNECTORS

Line Taps



- Wide Range, Universal and Reversible Figure H-shaped 6061-T6 Aluminum Connector
- For Copper, Aluminum, ACSR and Compact Conductors
- Conductors are Separated In A & B Grooves
- Bendable Taps Secure both Run and Tap Conductors Freeing the Formable Ribs Provide Broad Contact Area
- Massive Aluminum Design Minimizes Corrosion
- Prefilled with Anti-Oxidant Joint Compound

CAT. NO.	CONDUCTOR RANGE										INSTALLATION INFO.				CTN QTY
	STANDARD CONDUCTOR						COMPACT CONDUCTOR				CONN LENGTH	DIE NO.	NO. OF INDENTS		
	A GROOVE			BGROOVE			A GROOVE		BGROOVE				MECH	HYD	
	ACSR	STR.	SOL.	ACSR	STR.	SOL.	ACSR	STR.	ACSR	STR.					
90430	-	-	1	-	8	8	-	-	-	-	13/16"	5/8 BG	3	-	10
	3	2	2	-	10	10	-	-	-	-					
	4	3	3	-	12	12	-	-	-	-					
	6	4	4	-	14	14	-	-	-	-					
	6	-	-	-	-	-	-	-	-	-					
90433	-	1	-	-	1	-	1	1	1	1	1-7/16"	0	4	2	10
	2	2	2	2	2	2	2	2	2	2					
	3	3	3	3	3	3	3	3	3	3					
	4	4	4	4	4	4	4	4	4	4					
	6	6	6	6	6	6	6	6	6	6					
90435	-	2/0	2/0	-	1	1/0	2/0	2/0	1	1	1-11/16"	0	5	2	10
	1/0	1/0	1/0	2	2	1	1/0	2	2	-					
	1	1	1	3	3	3	1	1	3	3					
	2	2	-	4	4	4	2	2	4	4					
	3	-	-	6	6	6	-	-	6	6					
90454	-	2/0	2/0	-	1	1	2/0	2/0	1	1	1-1/8"	0	5	2	10
	1/0	1/0	1/0	2	2	2	1/0	1/0	2	2					
	1	1	1	3	3	3	1	1	3	3					
	2	2	2	4	4	4	2	2	4	4					
	3	3	-	6	6	-	-	-	6	6					
90462	4/0	4/0	4/0	4/0	4/0	4/0	266 - 18/1	266	266 - 18/1	266	1-3/8"	0	5	2	10
	3/0	3/0	3/0	3/0	3/0	3/0	4/0	250	4/0	250					
	2/0	2/0	2/0	2/0	2/0	2/0	3/0	4/0	3/0	4/0					
	1/0	1/0	-	1/0	1/0	-	2/0	3/0	2/0	3/0					
	-	-	4/0	-	3/0	3/0	-	-	-	-					
90439	-	4/0	3/0	2/0	2/0	2/0	3/0	3/0	3/0	3/0	1-13/16"	0	5	2	10
	2/0	3/0	2/0	1/0	1/0	-	2/0	2/0	2/0	2/0					
	1/0	2/0	-	1	-	-	1/0	1/0	1/0	1/0					
	-	-	-	-	-	1/0	-	-	-	-					
	-	-	-	-	1	1	-	-	1	1					
90440	-	-	4/0	2	2	2	3/0	3/0	2	2	1-13/16"	0	5	2	10
	-	3/0	3/0	3	3	3	2/0	-	3	3					
	2/0	2/0	-	4	4	4	-	-	4	4					
	1/0	-	-	6	6	6	-	-	6	6					
	-	-	-	-	-	1/0	-	-	-	-					
90444	-	-	-	-	1	1	-	-	1	1	1-13/16"	0	5	2	10
	-	-	-	2	2	2	266 - 18/1	266	2	2					
	4/0	4/0	-	3	3	3	-	-	-	-					
	3/0	-	-	4	4	4	-	-	-	-					
	-	-	-	6	6	6	-	-	-	-					
90447	-	-	-	-	-	-	266 - 18/1	266 - 18/1	266 - 18/1	266	2-7/16"	0	7	3	10
	4/0	4/0	-	4/0	4/0	-	-	250	-	250					
	3/0	3/0	-	3/0	3/0	-	4/0	4/0	4/0	4/0					