

# Streetlighting In-line Mechanical Break-Away Disconnect Kits



**67064 FUSIBLE**



**67065 NON-FUSED**

- Break-Away Design Separates Under Tension so wires don't break
- Ensures a Fully Insulated, Watertight and Submersible connection
- Fuse or Connecting Link stays in load side when separated
- Approved for a wide range of Aluminum or Copper conductors
- Accommodates Insulated Wire up to .38" Diameter
- Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- 30A 600V Max

**Kit Includes:**

EPDM Rubber Housing, Fuse Clips,  
Connecting Link (as Required),  
Silicone Lubricant. Fuse Not Included.

CAT. NO.	FUSED/ NON-FUSED	WIRE RANGE RUN	WIRE RANGE TAP	DIMENSIONS		CASE QTY
				DIAMETER	LENGTH	
67064	FUSED	#12 - #4	#12 - #4	1-1/16"	5-3/8"	25
67065	NON-FUSED	#12 - #4	#12 - #4	1-1/16"	5-3/8"	25

# Streetlighting Y-Type Mechanical Break-Away Disconnect Kits



**67066 FUSIBLE**



**67067 NON-FUSED**

- Break-Away Design Separates Under Tension so wires don't break
- Ensures a Fully Insulated, Watertight and Submersible connection
- Fuses or Connecting Link stay in load side when separated
- Approved for a wide range of Aluminum or Copper conductors
- Accommodates Insulated Wire up to .78" Dia.(Run) .38" Dia.(Tap)
- Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- 30A 600V Max

**Kit Includes:**

EPDM Rubber Housing, Fuse Clips,  
Connecting Link (as Required),  
Silicone Lubricant. Fuse Not Included.

CAT. NO.	FUSED/ NON-FUSED	WIRE RANGE RUN	WIRE RANGE TAP	DIMENSIONS		CASE QTY
				DIAMETER	LENGTH	
67066	FUSED	#14 - #2	#12 - #4	1-5/8"	9-3/4"	25
67067	NON-FUSED	#14 - #2	#12 - #4	1-5/8"	9-3/4"	10

# Y-Type Mechanical Streetlighting Kit



- Underground Mechanical Streetlight Splice Kit
- Watertight, Submersible & Re-Enterable
- Approved for use with aluminum or copper conductors
- Ensures a fully insulated, water-tight repair splice - no taping, heat shrink or mastic required
- Includes AL9CU Aluminum Connector

**Kit Includes:**

EPDM Rubber Housing, Fuse Clips,  
Connecting Link (as Required),  
Silicone Lubricant

CAT. NO.	KIT TYPE	WIRE RANGE COPPER	WIRE RANGE ALUMINUM	CONNECTOR HEX SIZE	DIMENSIONS		CASE QTY
					DIAMETER	LENGTH	
67062	Y TYPE	#14 - #4	#14 - #2	3/16"	1-5/8"	6-3/4"	25