Thin Wall Heat Shrink Tubing - Reels

- Flexible Polyolefin Heat Shrink Tubing
- 2:1 Shrink Ratio
- 600 Volt
- 257°F (125°C) Continuous Operation
- For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- Various Reel Lengths
- UL 224 Recognized

CAT NO.	LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	BAG QTY
68050	660′	BLACK	0.078″	0.029″	1 ROLL
68056	330′	BLACK	0.211″	0.098″	1 ROLL
68058	330′	BLACK	0.250″	0.117″	1 ROLL
68060	165′	BLACK	0.367″	0.176″	1 ROLL
68062	165′	BLACK	0.484″	0.234″	1 ROLL
68064	165′	BLACK	0.827″	0.390″	1 ROLL
68066	165′	BLACK	1.26″	0.590″	1 ROLL

Thin Wall Heat Shrink Tubing - Kits

68320

68321

CAT. NO.	KIT TYPE	CONTENTS				TOTAL PIECES
		LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	
			COLORED KIT			
68320	COLORED KIT	1.375″	(5) RED, (5) BLUE, (5) WHITE, (5) YELLOW	0.078″	0.029″	20
		1.375″	(5) RED, (5) BLUE, (5) WHITE, (5) YELLOW	0.098″	0.039″	20
		1.375″	(5) RED, (5) BLUE, (5) WHITE, (5) YELLOW	0.137″	0.059″	20
		1.375″	(5) RED, (5) BLUE, (5) WHITE, (5) YELLOW	0.212″	0.098″	20
		2.953″	(3) RED, (2) BLUE, (3) WHITE, (2) YELLOW	0.251″	0.117″	10
		2.953″	(1) RED, (2) BLUE, (1) WHITE, (1) YELLOW	0.370″	0.176″	5
		2.953″	(1) RED, (2) BLUE, (1) WHITE, (1) YELLOW	0.488″	0.236″	5
			BLACK KIT			
68321	BLACK KIT	1.375″	(20) BLACK	0.078″	0.029″	20
		1.375″	(20) BLACK	0.098″	0.039″	20
		1.375″	(20) BLACK	0.137″	0.059″	20
		1.375″	(20) BLACK	0.212″	0.098″	20
		2.953″	(10) BLACK	0.251″	0.117″	10
		2.953″	(5) BLACK	0.370″	0.176″	5
		2.953″	(5) BLACK	0.488″	0.236″	5