



Irreversible Grounding



- Made of Pure Electrolytic Copper - matches or exceeds conductor current carrying capacity
- Acceptable for direct burial in earth and concrete
- Provides a tap or pigtail-type connection from ground rods to grounding counterpoise or grid
- Conductor range #2 through 500 kcmil
- Suitable for use on Copperweld™ or copper clad cable
- Ground rod sizes 1/2", 5/8", 3/4", and 1"

DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	ROD/REBAR DIAMETER	DIMENSIONS INCHES		BOX QTY
			DEPTH/WIDTH	HEIGHT	
91500	#2-2/0	1/2"	.88	1.94"	50
91502	#2-2/0	5/8"	.88	1.97"	50
91504	#2-2/0	3/4"	.88	2.19"	40
91506	#2-2/0	1"	.88	2.55"	40
91510	2/0-250	1/2"	.88	1.40"	50
91512	2/0-250	5/8"	.88	2.14"	40
91514	2/0-250	3/4"	.88	2.19"	40
91516	2/0-250	1"	.88	2.45"	40
91520	250-500	5/8"	.88	2.14"	40
91522	250-500	3/4"	.88	2.44"	35
91524	250-500	1"	.88	2.45"	40



Fig 1



Fig 2

- Made of Pure Electrolytic Copper - matches or exceeds conductor current carrying capacity
- Acceptable for direct burial in earth and concrete
- Provides a tap or pigtail connection from ground rods to grounding counterpoise or grid
- Conductor range #6 through 500 kcmil
- Suitable for use on Copperweld™ or copper clad cable
- Ground rod sizes 1/2", 5/8", and 3/4"

DIMENSIONS = INCHES

CAT. NO.	FIG	CONDUCTOR/GROUND ROD TO CONDUCTOR WIRE RANGE		REBAR TO CONDUCTOR		DIMENSIONS INCHES		BOX QTY
		MAIN	TAP	MAIN	TAP	DEPTH/WIDTH	HEIGHT	
91530	1	#2 STR	#6 SOL	-	-	.88	1.94	75
91532	2	#2 STR	#6 SOL	-	-	.88	1.97	75
91534	2	250-1/0 1/2"-5/8" ROD	#6 STR-#8 SOL	#3(3/8")-#4(1/2")	#6 STR-#8 SOL	.88	2.19	50
91536	1	250-1/0 1/2"-5/8" ROD	#2 STR-#4 SOL	#3(3/8")-#4(1/2")	#2 STR	.88	2.55	15
91540	1	250-1/0 1/2"-5/8" ROD	2/0 STR-1/0 STR	#3(3/8")-#4(1/2")	2/0 STR-1/0 STR	.88	1.40	15
91542	1	250-1/0 1/2"-5/8" ROD	250-3/0 STR	#3(3/8")-#4(1/2")	250 MCM- 3/0 STR	.88	2.14	15
91544	1	500-250 3/4"-5/8" ROD	#2 STR-#4 STR	#5(5/8")-#6(3/4")	-	.88	2.19	15
91546	1	500-250 3/4"-5/8" ROD	2/0 STR-1/0 STR	#5(5/8")-#6(3/4")	2/0 STR-1/0 STR	.88	2.45	15
91547	1	500-250 3/4"-5/8" ROD	250-3/0 STR	#5(5/8")-#6(3/4")	250 MCM-3/0 STR	.88	2.14	15
91549	1	500-250 3/4"-5/8" ROD	500-350 MCM	#5(5/8")-#6(3/4")	500- MCM-350 MCM	.88	2.44	15