

Multi-Combination Ground/Neutral Bars

NEW

- Aluminum Neutral & Ground Bars - Multiple Wire Combinations
- Aluminum Bars are made from 6060-T6 Tin-Plated Aluminum
- Aluminum Bars are Dual Rated for Copper or Aluminum Conductors
- Available from 2 Circuit to 6 Circuit Feed & 5 Circuit to 17 Circuit Tap Configurations
- Range Taking
- 600V; 90°C
- UL 486A Listed
- Available in custom configurations upon request - consult factory



AVAILABLE
JULY 2020

DIMENSIONS = INCHES

CAT. NO.	NUMBER OF CIRCUITS		LENGTH	WIDTH	HEIGHT	BOX QTY
	1/0-14 AWG	6-14 AWG				
95195	2	5	2.29	.375	.625	400
95197	3	8	3.44	.375	.625	240
95199	4	11	4.63	.375	.625	200
95201	6	17	7.00	.375	.625	210

NEW

- Aluminum Neutral & Ground Bars - Multiple Wire Combinations
- Aluminum Bars are made from 6060-T6 Tin-Plated Aluminum
- Aluminum Bars are Dual Rated for Copper or Aluminum Conductors
- Screw Material: SAE1008 Zinc Plated Steel
- 600V; 90°C
- UL Recognized 486B




FIG 1




FIG 2




FIG 3




FIG 4



AVAILABLE
JULY 2020

DIMENSIONS = INCHES

CAT. NO.	FIG	CONDUCTOR ENTRY HOLE	CONDUCTOR RANGE	TOTAL NOS OF HOLE FOR CONDUCTOR	DIMENSIONS			BOX QTY
					LENGTH	WIDTH	HEIGHT	
95205	1	B C D	2 8 10 & 12	1 5 4	3.00	0.50	0.50	280
95207	2	B C D	2 8 10 & 12	1 7 6	3.53	0.50	0.50	240
95209	3	A B C D	1/0 2 8 10 & 12	1 1 9 9	4.86	0.50	0.50	160
95211	4	A B C D	1/0 2 8 10 & 12	1 1 12 12	5.88	0.50	0.50	160



GROUNDING

Neutral Bars