



Flexible Braided Jumper Straps



- Used wherever it is necessary to bridge expansion gaps, allow for misalignment or absorb vibration between moving parts
- To maintain continuity of ground electrode
- Prevent breakage of insulators, bushings or equipment due to misalignment during settling of substation foundations
- Manufactured from highly conductive extra flexible tinned copper braid flattened into a rectangular shape for greater flexibility
- Mounting pads on ends are made from tin-plated pure electrolytic copper for superior surface contact area

DIMENSIONS = INCHES

CAT. NO.	LENGTH	AMP RATING		APPROXIMATE CIRCULAR MILS	THICKNESS	PAD HOLE SIZE	BOX QTY
		INDOOR	OUTDOOR				
91620	12"	330	400	154,500	1/4"	1-1/2 X 9/16	10

Flexible Ground Braids



- Use for continuing the fault-carrying capacity of the cable shield for Bonding or Grounding Jumpers
- Use for shield & lead-sheath grounding, and is easily soldered to lead, copper & tinned metals
- Use to absorb expansion, misalignment, motion, or vibration of equipment
- Manufactured from high conductivity, woven process, annealed, tinned copper wire
- Use Multiple Layers to increase ampacity

DIMENSIONS = INCHES

CAT. NO.	WIDTH	LENGTH	EQUIVALENT AWG SIZE	BOX QTY
91630	3/8"	100'	9 AWG	10
91640	1/2"	100'	6 AWG	10

Green Grounding Pigtails



FIG 1



FIG 2

- Solid or Stranded Green 12 Gauge Wire
- Attached 10/32 x 3/8" Ground Screw with Easy-Start Tip

CAT. NO.	FIG	SIZE	BOX QTY
30774	1	GREEN SOLID 6-1/2" WITH 10/32 X 3/8 SCREW & END STRIPPED 5/8"	100
30775	2	GREEN STRANDED 8" WITH 10/32 X 3/8 GROUND SCREW & #10 FORK TERMINAL	100

Green Grounding Screws



- For Grounding of Switch & Outlet Boxes
- Hex Washer Head Slotted/Phillips 10/32 x 3/8" - Easy-Start Tip

CAT NO.	DESCRIPTION	BOX QTY
30772	10/32 X 3/8 GROUNDING SCREW	100

Green Grounding Clips



- Used with #10, #12, or #14 Copper or Aluminum Grounding Wire

CAT NO.	DESCRIPTION	BOX QTY
30773	GREEN GROUNDING CLIP	100