Vinyl Insulated Multiple-Stud Ring Terminals

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts
INSULATION MATERIAL: Vinyl
TERMINAL MATERIAL: Electro-Tin Plated Copper
FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
11452	RED	22-16	#6	.146	.339	.311	1.012	.441	.157	.067	.030	100	1,000
	RED	22-16	#8	.169									
	RED	22-16	#10	.209									
11454	BLUE	16-14	#6	.146	.339	.311	1.024	.453	.177	.091	.031	100	1,000
	BLUE	16-14	#8	.169									
	BLUE	16-14	#10	.209									
11456	YELLOW	12-10	#6	.146	.390	.350	1.205	.555	.248	.134	.039	100	1,000
	YELLOW	12-10	#8	.169									
	YELLOW	12-10	#10	.209									

Nylon Insulated Multiple-Stud Ring Terminals

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts
INSULATION MATERIAL: Nylon
TERMINAL MATERIAL:
Electro-Tin Plated Copper - Brazed Seam
FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
11462	RED	22-16	#6	.146	.339	.311	.996	.433	.157	.067	.030	100	1,000
	RED	22-16	#8	.169									
	RED	22-16	#10	.209									
11464	BLUE	16-14	#6	.146	.339	.311	.996	.433	.177	.091	.031	100	1,000
	BLUE	16-14	#8	.169									
	BLUE	16-14	#10	.209									
11466	YELLOW	12-10	#6	.146	.390	.350	1.154	.512	.252	.134	.039	100	1,000
	YELLOW	12-10	#8	.169									
	YELLOW	12-10	#10	.209									