




Vinyl Insulated Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

| | | | | | | | |
|-----|----|----|----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP | 3 | 4 | 7 | 10 | 15 | 20 | 24 |

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts

INSULATION MATERIAL: Vinyl


TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

| CAT. NO. | COLOR | WIRE SIZE AWG | W | F | L | B | C | D | T | BAG QTY | MASTER BAG QTY |
|----------|--------|---------------|------|------|------|------|------|------|------|---------|----------------|
| I2042 | RED | 22-16 | .157 | .335 | .827 | .394 | .067 | .157 | .016 | 100 | 1,000 |
| I2044 | BLUE | 16-14 | .157 | .335 | .827 | .394 | .091 | .177 | .016 | 100 | 1,000 |
| I2046 | BLUE | 16-14 | .197 | .335 | .827 | .394 | .091 | .177 | .016 | 100 | 1,000 |
| I2048 | YELLOW | 12-10 | .197 | .335 | .925 | .512 | .134 | .217 | .016 | 100 | 1,000 |

Nylon Insulated Double Crimp Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

| | | | | | | | |
|-----|----|----|----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP | 3 | 4 | 7 | 10 | 15 | 20 | 24 |

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass



DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

| CAT. NO. | COLOR | WIRE SIZE AWG | W | F | L | B | C | D | T | BAG QTY | MASTER BAG QTY |
|----------|--------|---------------|------|------|------|------|------|------|------|---------|----------------|
| I2052 | RED | 22-16 | .157 | .335 | .866 | .433 | .067 | .157 | .016 | 100 | 1,000 |
| I2054 | BLUE | 16-14 | .157 | .335 | .866 | .433 | .091 | .197 | .016 | 100 | 1,000 |
| I2056 | BLUE | 16-14 | .197 | .335 | .866 | .433 | .091 | .197 | .016 | 100 | 1,000 |
| I2058 | YELLOW | 12-10 | .197 | .335 | .925 | .512 | .134 | .256 | .016 | 100 | 1,000 |

Nylon Fully Insulated Double Crimp Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

| | | | | | | | |
|-----|----|----|----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP | 3 | 4 | 7 | 10 | 15 | 20 | 24 |

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

| CAT. NO. | COLOR | WIRE SIZE AWG | W | F | L | B | C | D | T | BAG QTY | MASTER BAG QTY |
|----------|-------|---------------|------|------|-------|------|------|------|------|---------|----------------|
| I2062 | RED | 22-16 | .157 | .412 | 1.063 | .394 | .067 | .157 | .016 | 100 | 1,000 |
| I2064 | BLUE | 16-14 | .157 | .413 | 1.063 | .394 | .091 | .177 | .016 | 100 | 1,000 |