




# Non-Insulated Butt Splice Connectors

**NEW**  
BULK PACKS



## MAXIMUM ELECTRIC CURRENT:

| AWG | 26  | 24 | 22 | 20 | 18 | 16 | 14 | 12 | 10 | 8  | 6  | 4   |
|-----|-----|----|----|----|----|----|----|----|----|----|----|-----|
| AMP | 5.5 | 7  | 9  | 12 | 17 | 18 | 30 | 35 | 50 | 70 | 95 | 125 |

MAXIMUM ELECTRIC RATING: 302°F (150°C) 600V

CONNECTOR MATERIAL: Electro-Tin Plated Tubular Copper

DIMENSIONS = INCHES

| CAT. NO. | WIRE SIZE AWG | L     | D    | DI   | BAG QTY | MASTER BAG QTY |
|----------|---------------|-------|------|------|---------|----------------|
| I2I02    | 26-22         | .472  | .083 | .051 | 100     | 1,000          |
| I2I02B   | 26-22         | .472  | .083 | .051 | 1,000   | 20,000         |
| I2I04    | 22-16         | .591  | .130 | .067 | 100     | 1,000          |
| I2I04B   | 22-16         | .591  | .130 | .067 | 1,000   | 20,000         |
| I2I06    | 16-14         | .591  | .154 | .091 | 100     | 1,000          |
| I2I06B   | 16-14         | .591  | .154 | .091 | 1,000   | 20,000         |
| I2I08    | 12-10         | .591  | .213 | .134 | 100     | 1,000          |
| I2I08B   | 12-10         | .591  | .213 | .134 | 1,000   | 10,000         |
| I2I10    | 8             | .827  | .276 | .181 | 100     | -              |
| I2I12    | 6             | 1.024 | .350 | .232 | 100     | -              |
| I2I14    | 4             | 1.142 | .445 | .307 | 100     | -              |
| I2I15    | 2             | 1.260 | .520 | .374 | 100     | -              |

# Non-Insulated Reducing Butt Splice Connector



## MAXIMUM ELECTRIC CURRENT:

| AWG | 26  | 24 | 22 | 20 | 18 | 16 | 14 | 12 | 10 | 8  | 6  | 4   |
|-----|-----|----|----|----|----|----|----|----|----|----|----|-----|
| AMP | 5.5 | 7  | 9  | 12 | 17 | 18 | 30 | 35 | 50 | 70 | 95 | 125 |

MAXIMUM ELECTRIC RATING: 302°F (150°C) 600 Volts

TERMINAL MATERIAL: Electro-Tin Plated Copper

DIMENSIONS = INCHES

| CAT. NO. | WIRE RANGE AWG | L     | D    | DI   | D2   | BAG QTY | MASTER BAG QTY |
|----------|----------------|-------|------|------|------|---------|----------------|
| I2I16    | 16-14 TO 22-18 | .591  | .154 | .067 | .091 | 100     | 1,000          |
| I2I17    | 12-10 TO 22-18 | .787  | .213 | .067 | .134 | 100     | 1,000          |
| I2I18    | 12-10 TO 16-14 | .787  | .213 | .091 | .138 | 100     | 1,000          |
| I2I19    | 8 TO 16-14     | .827  | .067 | .091 | .181 | 100     | 1,000          |
| I2I20    | 8 TO 12-10     | .827  | .067 | .138 | .181 | 100     | 1,000          |
| I2I21    | 6 TO 8         | 1.024 | .351 | .181 | .232 | 100     | 1,000          |

# Vinyl Insulated Butt Splice Connectors



## MAXIMUM ELECTRIC CURRENT:

| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 | 8  | 6  | 4   | 2   |
|-----|----|----|----|----|----|----|----|----|----|-----|-----|
| AMP | 9  | 12 | 17 | 18 | 30 | 35 | 50 | 70 | 95 | 125 | 170 |

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts

CONNECTOR MATERIAL: Electro-Tin Plated Tubular Copper

INSULATION MATERIAL: Vinyl

FEATURES: Expanded Insulation

DIMENSIONS = INCHES

| CAT. NO. | COLOR  | WIRE SIZE AWG | L     | D    | DI   | MATERIAL       | BAG QTY | MASTER BAG QTY |
|----------|--------|---------------|-------|------|------|----------------|---------|----------------|
| I0I82    | RED    | 22-16         | .969  | .157 | .067 | COPPER PLATE   | 100     | 1,000          |
| I0I84    | BLUE   | 16-14         | .969  | .177 | .091 | COPPER PLATE   | 100     | 1,000          |
| I0I86    | YELLOW | 12-10         | 1.043 | .248 | .134 | COPPER PLATE   | 100     | 1,000          |
| I2I28    | RED    | 8             | 1.398 | .335 | .177 | TUBULAR COPPER | 100     | -              |
| I2I30    | BLUE   | 6             | 1.772 | .413 | .232 | TUBULAR COPPER | 100     | -              |
| I2I32    | YELLOW | 4             | 2.067 | .488 | .307 | TUBULAR COPPER | 100     | -              |
| I2I34    | RED    | 2             | 2.165 | .610 | .374 | TUBULAR COPPER | 100     | -              |