


# Heat Shrinkable - Nylon Fully Insulated Male Disconnects

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 300 Volts  
 SHRINK TEMP: 302°F (150°C)  
 RESISTANT TEMP: -40°F ~ 221°F (-40°C ~ 105°C)  
 INSULATION MATERIAL: Nylon & High Density PE Heat Shrink  
 TERMINAL MATERIAL: Electro-Tin Plated Brass



DIMENSIONS = INCHES


CAT. NO.	COLOR	WIRE SIZE AWG	TAB SIZE	L	W	D	BAG QTY	MASTER BAG QTY
I2277	RED	22-16	.032 X .250	1.516	.25	.256	100	1,000
I2278	BLUE	16-14	.032 X .250	1.555	.25	.256	100	1,000
I2279	YELLOW	12-10	.032 X .250	1.555	.26	.295	100	1,000

# Heat Shrinkable - Bullet Disconnects

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 300 Volts  
 SHRINK TEMP: 302°F (150°C)  
 RESISTANT TEMP: 14°F ~ 221°F (-26°C ~ 105°C)  
 INSULATION MATERIAL: High Density PE Heat Shrink  
 DOUBLE CRIMP: Extended Copper Sleeve  
 TERMINAL MATERIAL: Electro-Tin Plated Brass  
 FEATURES: Serrated Barrel



DIMENSIONS = INCHES


CAT. NO.	COLOR	WIRE SIZE AWG	W	D	L	BAG QTY	BOX QTY
I2312	RED	22-16	.157	.217	1.299	100	1,000
I2314	BLUE	16-14	.157	.236	1.299	100	1,000
I2316	BLUE	16-14	.197	.236	1.299	100	1,000
I2318	YELLOW	12-10	.197	.319	1.398	100	1,000

# Heat Shrinkable - Nylon Fully Insulated Bullet Disconnects

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14
AMP	3	4	7	10	15

MAXIMUM ELECTRIC RATING: 300 Volts  
 SHRINK TEMP: 302°F (150°C)  
 INSULATION MATERIAL: Nylon with High Density PE Heat Shrink  
 TERMINAL MATERIAL: Electro-Tin Plated Tubular Brass



DIMENSIONS = INCHES



CAT. NO.	COLOR	WIRE SIZE AWG	DIA (W)	L	W	D	BAG QTY	MASTER BAG QTY
I2319	RED	22-16	.157	1.654	.25	.256	100	1,000
I2320	BLUE	16-14	.157	1.555	.25	.256	100	1,000

# Heat Shrinkable - Fully Insulated Receptacle Disconnects

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 300 Volts  
 SHRINK TEMP: 302°F (150°C)  
 RESISTANT TEMP: 14°F ~ 221°F (-26°C ~ 105°C)  
 INSULATION MATERIAL: Nylon with High Density PE Heat Shrink  
 DOUBLE CRIMP: Extended Copper Sleeve  
 TERMINAL MATERIAL: Electro-Tin Plated Brass  
 FEATURES: Serrated Barrel



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	W	D	L	BAG QTY	MASTER BAG QTY
I2322	RED	22-16	.154	.256	1.594	100	1,000
I2324	BLUE	16-14	.154	.295	1.594	100	1,000