

Nylon Insulated Ferrules - DIN Standard



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

TERMINAL MATERIAL:


Electro-Tin Plated Tubular Copper

INSULATION MATERIAL: Nylon Insulation

FEATURES: Flared Barrel, Expanded Insulation

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600V

COLOR CODE: DIN Standard



DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	COLOR	F	B	L	W	D	C	BAG QTY	MASTER BAG QTY
I2702	26	YELLOW	.236	.173	.409	.075	.043	.031	100	1,000
I2704	26	YELLOW	.315	.173	.488	.075	.043	.031	100	1,000
I2706	24	TURQUOISE	.236	.173	.409	.075	.043	.031	100	1,000
I2708	24	TURQUOISE	.315	.173	.488	.075	.043	.031	100	1,000
I2708B	24	TURQUOISE	.315	.173	.488	.075	.043	.031	1,000	20,000
I2710	22	WHITE	.236	.236	.472	.102	.051	.039	100	1,000
I2712	22	WHITE	.315	.236	.551	.102	.051	.039	100	1,000
I2714	22	WHITE	.394	.236	.630	.102	.051	.039	100	1,000
I2716	20	GREY	.236	.248	.472	.110	.059	.047	100	1,000
I2718	20	GREY	.315	.248	.551	.110	.059	.047	100	1,000
I2720	20	GREY	.394	.260	.630	.110	.059	.047	100	1,000
I2722	20	GREY	.472	.260	.709	.110	.059	.047	100	1,000
I2724	18	RED	.236	.248	.472	.118	.067	.055	100	1,000
I2726	18	RED	.315	.248	.551	.118	.067	.055	100	1,000
I2728	18	RED	.394	.248	.630	.118	.067	.055	100	1,000
I2728B	18	RED	.394	.248	.630	.118	.067	.055	1,000	10,000
I2730	18	RED	.472	.248	.709	.118	.067	.055	100	1,000
I2732	16	BLACK	.315	.248	.551	.138	.079	.067	100	1,000
I2732B	16	BLACK	.315	.248	.551	.138	.079	.067	1,000	10,000
I2734	16	BLACK	.394	.248	.630	.138	.079	.067	100	1,000
I2734B	16	BLACK	.394	.248	.630	.138	.079	.067	100	1,000
I2736	16	BLACK	.472	.248	.709	.138	.079	.067	100	1,000
I2736B	16	BLACK	.472	.248	.709	.138	.079	.067	1,000	10,000
I2738	16	BLACK	.709	.248	.945	.138	.079	.067	100	1,000
I2740	14	BLUE	.315	.165	.551	.165	.098	.087	100	1,000
I2740B	14	BLUE	.315	.165	.551	.165	.098	.087	1,000	4,000
I2742	14	BLUE	.472	.165	.709	.165	.098	.087	100	1,000
I2742B	14	BLUE	.472	.165	.709	.165	.098	.087	1,000	4,000
I2746	14	BLUE	.709	.165	.945	.165	.098	.087	100	1,000
I2748	12	GREY	.394	.189	.669	.189	.126	.110	100	1,000
I2750	12	GREY	.472	.189	.787	.189	.126	.110	100	1,000
I2752	12	GREY	.709	.189	1.024	.189	.126	.110	100	1,000
I2754	10	YELLOW	.472	.248	.787	.248	.154	.138	100	1,000
I2754B	10	YELLOW	.472	.248	.787	.248	.154	.138	1,000	4,000
I2756	10	YELLOW	.709	.248	1.024	.248	.154	.138	100	1,000
I2758	8	RED	.472	.299	.886	.299	.193	.177	100	-
I2760	8	RED	.709	.299	1.102	.299	.193	.177	100	-
I2762	6	BLUE	.472	.346	.945	.524	.236	.220	100	-
I2764	6	BLUE	.709	.346	1.102	.524	.236	.220	100	-
I2766	4	YELLOW	.630	.441	1.102	.441	.303	.287	100	-
I2768	4	YELLOW	.709	.441	1.181	.441	.303	.287	100	-
I2770	4	YELLOW	.886	.441	1.417	.441	.303	.287	100	-
I2772	2	RED	.630	.500	1.181	.500	.343	.327	100	-
I2774	2	RED	.709	.500	1.181	.500	.343	.327	100	-
I2776	2	RED	.984	.500	1.535	.500	.343	.327	100	-