



Strut to Beam Clamp with Square U-Bolt



- For 13/16" & 1-5/8" Channel
- Design load 1,200 lbs. when used in pairs
- Zinc Electroplate Finish

CAT. NO.	DESCRIPTION	BOX QTY
17462	BEAM CLAMP FOR 13/16" & 1-5/8" CHANNEL	25

Strut to Beam Clamp with Square U-Bolt



- For 2-7/16" & 3-1/4" Channel
- Design load 1,200 lbs. when used in pairs
- Zinc Electroplate Finish

CAT. NO.	DESCRIPTION	BOX QTY
17464	BEAM CLAMP FOR 2-7/16" & 3-1/4" CHANNEL	25

Strut Fitting Torque Values

- The following are the torque values used for determining the load ratings of fittings when attached to channel framing as specified in the Metal Framing Manufacturers Association (MFMA) Standard #2

THREAD SIZE	TORQUE		
	IN. LB.	FT. LB.	NM
1/4"	72	6	8.1
3/8"	228	19	25.8
1/2"	600	50	67.8

Beam Clamp Torque Values

- For beam clamps or other applications the following torque values from Manufacturer's Standardization Society (MSS) SP-69 are recommended unless otherwise specified

THREAD SIZE	TORQUE		
	IN. LB.	FT. LB.	NM
1/4"	40	3.3	4.5
3/8"	60	5.0	6.8
1/2"	125	10.4	14.1