



# Digital AC Clamp Meter with Temperature

- AC Current: 6A/60A/600A  $\pm(2.5\%+10)$
- AC Voltage: 600V  $\pm(1.2\%+10)$   
600mV/6V/60V  $\pm(1.0\%+10)$
- DC Voltage: 600V  $\pm(1.0\%+2)$   
600mV/6V/60V  $\pm(0.8\%+2)$
- Resistance: 600 $\Omega$ /6k $\Omega$ /60k $\Omega$ /600k $\Omega$ /6M $\Omega$   $\pm(1.2\%+2)$   
60M $\Omega$   $\pm(2.0\%+2)$
- Temperature Range: -4 $^{\circ}$ F to 1832 $^{\circ}$ F (-20 $^{\circ}$ C to 260 $^{\circ}$ C)  $\pm(2.0\%+4)$
- Display: 6000 Counts
- Jaw Opening To 1.0"
- Continuity Buzzer: <50V $\Omega$
- Diode Open Voltage: 3.2V
- Non-Contact Voltage Detector
- Auto & Manual Ranging
- Backlit Display
- Data Hold
- Worklight
- Safety Rating: Cat III 600V
- Low Battery Display
- Auto Power Off
- Power Source: 3x 1.5V AAA Batteries (Included)
- Dimensions: 8.9" X 3.1" X 1.4"
- Weight: 8.48 OZ

CAT. NO.	DESCRIPTION	MOQ
MS2009C	DIGITAL AC CLAMP METER	1



TOOLS  
Meters & Testers



# AC 1000A Digital Clamp Meter

- DC Voltage: 1000V with basic accuracy  $\pm(0.8\%+4)$   
60mV/600mV/6V/60V/600V  $\pm(0.5\%+5)$
- AC Voltage: 750V  $\pm(0.8\%+4)$   
60mV/600mV/6V/60V/600V  $\pm(0.6\%+5)$
- AC Current: 60A/600A/1000A  $\pm(2.0\%+8)$
- Resistance: 600 $\Omega$ /6k $\Omega$ /60k $\Omega$ /600k $\Omega$   $\pm(0.8\%+3)$   
6M $\Omega$ /60 $\Omega$   $\pm(1.2\%+3)$
- Display: 6000 Counts
- Continuity Buzzer: <50 $\Omega$
- Jaw Opening: 1.6"
- Auto & Manual Ranging
- Auto Power Off
- Relative Measurement
- Non-Contact Voltage Detector
- Open Voltage Diode: 3.2V
- Backlit Display
- Data hold
- Safety Rating: CAT III 1000V/ CAT IV 600V
- Low Battery Display
- Dimensions: 9.37" x 3.6" x 1.9"
- Weight: 13.6 OZ.

CAT. NO.	DESCRIPTION	MOQ
MS2025A	AC 1000A DIGITAL CLAMP METER	1

