

# Wall Mount Occupancy/Vacancy Sensor - PIR



- The Passive Infrared (PIR) Sensor detects motion by sensing the difference between body heat and ambient room temperature
- PIR Occupancy Sensor works best in offices, conference rooms and other commonly used areas without obstructions
- Vacancy Setting allows for Manual ON/Auto OFF Function
- Auto ON/OFF & Manual ON/Auto OFF
- 30Ft Range When Mounted at 4Ft Height
- LED Indicator for visibility in darkened rooms
- Adjustable Light Level Sensitivity Settings
- Time Delay Off setting is adjustable from 5 Seconds to 30 minutes
- Removable Cover with mode settings and dip switch adjustments
- Decorative Wall Plate Included
- Polycarbonate
- Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- Conforms to California Title 24 Energy Code
- 60Hz
- Neutral Required

CAT. NO.	COLOR	SWITCH TYPE	SWITCH RATING	INCANDESCENT/FLUORESCENT RATING	COVERAGE	VOLTAGE	LED WATTS	TIME DELAY	CASE QTY
80520	IVORY	AUTO ON/OFF MANUAL ON/AUTO OFF	SINGLE POLE	800W @ 120V 1200W @ 277V	180°	120-277V	300W	5 SEC-30 MIN	50
80521	WHITE	AUTO ON/OFF MANUAL ON/AUTO OFF	SINGLE POLE	800W @ 120V 1200W @ 277V	180°	120-277V	300W	5 SEC-30 MIN	50
80540	WHITE	AUTO ON/OFF MANUAL ON/AUTO OFF	SINGLE POLE 3-WAY	800W @ 120V 1200W @ 277V	180°	120-277V	300W	5 SEC-30 MIN	50

# Wall Mount Occupancy/Vacancy Sensor - No Neutral - PIR



- The Passive Infrared (PIR) Sensor detects motion by sensing the difference between body heat and ambient room temperature
- Wall switch works best in offices, conference rooms and other commonly used areas
- Vacancy Setting allows for Manual ON/Auto OFF Function
- Auto ON/OFF & Manual ON/Auto OFF
- 30Ft Range When Mounted at 4Ft Height
- LED indicator for visibility in darkened rooms
- Adjustable Light Level Sensitivity Settings
- Time delay Off setting is adjustable from 5 Seconds to 30 minutes
- Removable Cover with mode settings and dip switch adjustments
- Decorator Wall Plate Included
- Polycarbonate
- Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- Conforms to California Title 24 Energy Code
- 60Hz
- No Neutral Required

CAT. NO.	COLOR	SWITCH TYPE	SWITCH CONFIGURATION	INCANDESCENT/FLUORESCENT RATING	COVERAGE	VOLTAGE	LED WATTS	TIME DELAY	CASE QTY
80528	WHITE	AUTO ON/OFF MANUAL ON/AUTO OFF	SINGLE POLE	800W @ 120V 1200W @ 277V	180°	120-277V	300W	5 SEC - 30 MIN	50
80532	WHITE	AUTO ON/OFF MANUAL ON/AUTO OFF	SINGLE POLE 3 WAY	800W @ 120V 1200W @ 277V	180°	120-277V	300W	5 SEC - 30MIN	50