

Coaxial Compression Connectors

- Visible Post Design - User friendly, eliminates damage to cable foil & dielectric
- Improved signal performance
- Water-tight seal for outdoor applications & superior durability in all climates
- 21mm (.827") or 35.7mm (1.40") travel compression crimp protects the center conductor from damage
- Permanent connections do not pull out or become loose - >50 lbs Retention Force
- Large tapered entry allows for easy cable insertion
- Gold Plated contacts
- RF signal containment ensures strong signal
- Bandwidth: 0-3 GHz
- Return Loss: -30 db @1 GHz
- Insertion Loss: < .1db @ 1 GHz
- Shielding Effectiveness: 80 db
- Operating Temperature: -40°F (-40°C) ~ 140°F (60°C)
- Cable Retention: >50 lbs
- Meets or Exceeds all SCTE specifications
- 45073, 45077 & 45079 are all brass exterior construction for superior durability

USED BY CABLE TV
& SATELLITE
COMPANIES

COMPRESSION
PUSH-LOCK
DESIGN

CAT. NO.	TYPE	DESCRIPTION	BAG QTY
F MALE COMPRESSION			
45075	RG6	STD & TRI SHIELD	10
45071	RG6	STD & TRI SHIELD	100
F MALE COMPRESSION - HI-CONTINUITY			
45072	RG6U	STD, TRI & QUAD SHIELD	10
45078	RG6U	STD, TRI & QUAD SHIELD	100
45076	RG59	STD, TRI & QUAD SHIELD	10
F MALE COMPRESSION - HI-CONTINUITY - ALL BRASS (PREMIER CONNECTOR)			
45073	RG6U	STD, TRI & QUAD SHIELD	10
45079	RG6U	STD, TRI & QUAD SHIELD	100
45077	RG11U	STD, TRI & QUAD SHIELD	10
BNC MALE COMPRESSION			
45102	RG6U QUAD SHIELD	STD, TRI & QUAD SHIELD	10
45106	RG59U QUAD SHIELD	STD, TRI & QUAD SHIELD	10
RCA MALE COMPRESSION			
45112	RG6U QUAD SHIELD	STD, TRI & QUAD SHIELD	10
45116	RG59U QUAD SHIELD	STD, TRI & QUAD SHIELD	10



45071/45075



45072/45078



45073/45079



45077



45076



45102, 45106



45112, 45116



WIRING DEVICES

Voice/Datacom - Coaxial Connectors