
# Self-Adhesive TPE Gasketing

**Properties:**


- Thermo-Plastic Elastomer (TPE)
- Good abrasion resistance
- Moisture resistant
- BHMA certified to ANSI/BHMA A156.22 performance tests for heat, cold, air infiltration and energy performance
- Adhesive specifications shown on page G9
- Rigid base with flexible elastomeric fins
- Flame resistant
- Temperature range -60˚F to 275˚F
- Anti-microbial: treated with an anti-microbial additive to inhibit the growth of microorganisms
- REACH and RoHS compliant





## TPE Batwing Smoke Seal

**5020B** Brown
**5020C** Charcoal
**5020W** White
**5020CL** Clear

Available in 36", 48", 72", 84", 96" and 108" lengths









## TPE Double Batwing Smoke Seal

Superior sealing characteristics against smoke, air & sound

**5025B** Brown
**5025C** Charcoal
**5025W** White
**5025CL** Clear

Available in 36", 48", 72", 84", 96" and 108" lengths








## TPE Batwing Smoke Seal (Kerf Press-in)

**5021B** Brown
**5021C** Charcoal
**5021W** White

Fits Kerf 1/8" wide x 7/16" deep

Available in 36", 48", 84", 96" and 108" lengths




* Anti-microbial not available in clear