

1332/1432 Hinge Options

Application	Hinge Cap	Optional Accuride Hardware Kit		Door Thickness		Maximum Tab		Minimum Gap		Door Clearance			
Inset	35 mm			mm	inches	mm	inches	mm	inches	mm	inches		
				19.0	3/4	8.0	5/16	2.3 ■◆	3/32 ■◆	1.4	1/16		
				20.6	13/16	9.0 ■	11/32 ■	1.8 ●	1/16 ●	0.3	1/64		
				• Requires hinge lateral adjustment to acheive door gap				• May require notching		◆ For smaller gap, increase tab			
				19.0	3/4	8.0	5/16	3.3 ■◆	1/8 ■◆	5.4	7/35		
		20.6								13/16	3.8	5/32	
		■ May require notching.								◆ For smaller door gap, increase tab.			
				19.0	3/4	6.5	1/4	1.8 ●	1/16 ●	2.4	3/32		
										20.6	13/16	8.0	1/32
		Inset for Thick Doors	40 mm	41800394	Zinc Self Close	19.0	3/4	15.0	19/32	2.3	3/32	14.4	9/16
20.6	13/16					12.8	1/2						
22.2	7/8					11.2	7/16						
23.8	15/16					9.6	3/8						
25.4	1					8.0	5/16						
27.0	1-1/16					6.4	1/4						
28.6	1-1/8					4.8	3/16						
30.2	1-3/16					3.2	1/8						
31.8	1-1/4					1.6	1/16						
						19.0	3/4					8.0	5/16
				20.6	13/16	5.4	7/32						
				22.2	7/8	3.8	5/32						
				23.8	15/16	2.2	3/32						
				25.4	1	6.0	1/32						
				27.0 ◆	1-1/16 ◆	2.0	3/32						
				28.6 ◆	1-1/8 ◆	4.0	1/32						
				30.2 ○◆	1-3/16 ○◆	11.0	7/16	1.6	1/16				
				31.8 ○◆	1-1/4 ○◆	14.0	9/16 ○	0.0	0				
				○ Requires 3 mm (1/8") notch to the back of the door. ◆ Requires 1 spacer, 3 mm (1/8")									
											Overlay Amount		
Overlay	40 mm	41800292	Zinc Self Close	19.0	3/4	15.0	19/32	11.7	7/16	0.4	1/64		

For Additional Hinges - add 1 more spacer to secondary hinges.

Note: On thicker doors, mortise hinge cup into door back to improve door-to-slide clearance.

CAUTION: For doors under 36" tall, hinge carrier strip needs to be modified. Hinge carrier strip required for all doors.