

Safety Data Sheet



LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

Safety Data Sheet dated 4/4/2018, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name: CATALIZZATORE non ingiallente- non-yellowing catalyst

Other means of identification

Trade code: LCB057

Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Catalyst for paints and varnishes

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, Acute Tox. 4, Harmful if inhaled.

⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.

⚠ Warning, STOT SE 3, May cause respiratory irritation.

⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water/...
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/ doctor/if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see ... On this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	Hexamethylene diisocyanate, oligomers (biuret type)	CAS: 28182-81-2 EC: 939-340-8 REACH No.: 01-2119970543-34	A.1/4/Inhal Acute Tox. 4 H332 A.4.2/1 Skin Sens. 1 H317 A.8/3 STOT SE 3 H335
>= 30% - < 40%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	B.6/3 Flam. Liq. 3 H226 A.8/3 STOT SE 3 H336
>= 5% - < 7%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	B.6/3 Flam. Liq. 3 H226 A.1/4/Dermal Acute Tox. 4 H312 A.1/4/Inhal Acute Tox. 4 H332 A.2/2 Skin Irrit. 2 H315 A.8/3 STOT SE 3 H335 A.9/2 STOT RE 2 H373 A.10/1 Asp. Tox. 1 H304
>= 1% - < 3%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	B.6/2 Flam. Liq. 2 H225 CAN-HAE/C3 Aquatic Chronic 3 H412 A.1/4/Inhal Acute Tox. 4 H332 A.9/2 STOT RE 2 H373 A.10/1 Asp. Tox. 1 H304
>= 0.1% - < 0.3%	hexamethylene-di-isocyanate	Index number: 615-011-00-1 CAS: 822-06-0 EC: 212-485-8 REACH No.: 01-2119457571-37	A.1/1/Inhal Acute Tox. 1 H330 A.1/4/Oral Acute Tox. 4 H302 A.8/3 STOT SE 3 H335 A.2/2 Skin Irrit. 2 H315 A.4.1/1 Resp. Sens. 1 H334

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

LCB057/1

Page n. 2 of 10

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:
Do NOT induce vomiting.

In case of Inhalation:
If breathing is irregular or stopped, administer artificial respiration.
In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed
None

Indication of immediate medical attention and special treatment needed, if necessary
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:
None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media
Suitable extinguishing media:
In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:
None in particular.

Specific hazards arising from the hazardous product
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:
None

Explosive properties: N.D. in volume
Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

Methods and material for containment and cleaning up
Wash with plenty of water.

7. Handling and storage

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not use on extensive surface areas in premises where there are occupants.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

8. Exposure controls/personal protection

Control parameters

Hexamethylene diisocyanate, oligomers (biuret type) - CAS: 28182-81-2
 EU - STEL: 1 mg/m³
 n-butyl acetate - CAS: 123-86-4
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
 xylene [4] - CAS: 1330-20-7
 EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
 ethylbenzene - CAS: 100-41-4
 EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
 hexamethylene-di-isocyanate - CAS: 822-06-0
 ACGIH - TWA(8h): 0.005 ppm - Notes: URT irr, resp sens

DNEL Exposure Limit Values

Hexamethylene diisocyanate, oligomers (biuret type) - CAS: 28182-81-2
 Worker Industry: 0.5 mg/m³ - Worker Professional: 0.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 1 mg/m³ - Worker Professional: 1 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 n-butyl acetate - CAS: 123-86-4
 Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 hexamethylene-di-isocyanate - CAS: 822-06-0
 Worker Industry: 0.07 mg/m³ - Worker Professional: 0.07 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 0.07 mg/m³ - Worker Professional: 0.07 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 0.035 mg/m³ - Worker Professional: 0.035 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 0.035 mg/m³ - Worker Professional: 0.035 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

Hexamethylene diisocyanate, oligomers (biuret type) - CAS: 28182-81-2
 Target: Microorganisms in sewage treatments - Value: 6.46 mg/l
 n-butyl acetate - CAS: 123-86-4
 Target: Fresh Water - Value: 0.18 mg/l
 Target: Marine water - Value: 0.018 mg/l
 Target: Intermittent emission - Value: 0.36 mg/l
 Target: Freshwater sediments - Value: 0.98 mg/kg
 Target: Marine water sediments - Value: 0.098 mg/kg
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l
 Target: Soil (agricultural) - Value: 0.09 mg/kg
 xylene [4] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.32 mg/l
 Target: Marine water - Value: 0.32 mg/l
 Target: Intermittent emission - Value: 0.32 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil (agricultural) - Value: 2.31 mg/kg
 ethylbenzene - CAS: 100-41-4
 Target: Fresh Water - Value: 0.1 mg/l
 Target: Marine water - Value: 0.01 mg/l
 Target: Freshwater sediments - Value: 13.7 mg/kg
 Target: Soil (agricultural) - Value: 2.68 mg/kg
 Target: Intermittent emission - Value: 0.1 mg/l
 Target: Microorganisms in sewage treatments - Value: 9.6 mg/l
 hexamethylene-di-isocyanate - CAS: 822-06-0
 Target: Fresh Water - Value: 0.0774 mg/l
 Target: Marine water - Value: 0.00774 mg/l
 Target: Freshwater sediments - Value: 0.01334 mg/kg
 Target: Marine water sediments - Value: 0.001334 mg/kg
 Target: Intermittent emission - Value: 0.774 mg/l
 Target: Microorganisms in sewage treatments - Value: 8.42 mg/l
 Target: Soil (agricultural) - Value: 0.0026 mg/kg
 Appropriate engineering controls
 None
 Individual protection measures, such as personal protective equipment (PPE)
 Eye protection:
 Eye glasses with side protection. (EN166)
 Protection for skin:
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
 Protection for hands:
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)
 Respiratory protection:
 Use respiratory protection where ventilation is insufficient or exposure is prolonged.
 Use adequate protective respiratory equipment.
 Thermal Hazards:
 None

9. Physical and chemical properties

Appearance and colour:	colourless fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 126 °C
Flash point:	> 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.5% - 1.6% Vol. (n-butyl acetate)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.980 - 1.000
Solubility in water:	partial, reacts
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity
 It may generate dangerous reactions (See subsections below)
 Chemical stability
 It may generate dangerous reactions (See subsections below)
 Possibility of hazardous reactions
 It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth, alloys in powder or vapours) and powerful reducing agents.
 It may generate toxic gases on contact with oxidising mineral acids, and powerful oxidising agents.
 It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
 Conditions to avoid
 Avoid accumulating electrostatic charge.
 Incompatible materials
 Avoid contact with combustible materials. The product could catch fire.

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

Hazardous decomposition products
None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

CATALIZZATORE non ingiallente- non-yellowing catalyst

a) acute toxicity

The product is classified: Acute Tox. 4 H332

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

The product is classified: STOT SE 3 H335; STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

Hexamethylene diisocyanate, oligomers (biuret type) - CAS: 28182-81-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation Mist - Species: Rat = 400 mg/m3 - Duration: 4h - Source: OCSE 403

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

hexamethylene-di-isocyanate - CAS: 822-06-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 710 mg/kg

Test: LC50 - Route: Skin - Species: Rabbit = 570 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 0.124 mg/l - Duration: 4h - Source: OCSE 403

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

ethylbenzene - Group 2B.

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CATALIZZATORE non ingiallente- non-yellowing catalyst

Not classified for environmental hazards

No data available for the product

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 2.4 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 4.6 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Duration h: 168

hexamethylene-di-isocyanate - CAS: 822-06-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 82.8 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 89.1 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 77.4 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 11.7 mg/l - Duration h: 72

Persistence and degradability

Hexamethylene diisocyanate, oligomers (biuret type) - CAS: 28182-81-2

Biodegradability: Non-readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 70-80 - Notes: N.A.

hexamethylene-di-isocyanate - CAS: 822-06-0

Biodegradability: Non-readily biodegradable - Test: Biochemical oxygen demand - Duration h: 28 days - %: 42 - Notes: N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst



UN number	
TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint
Transport hazard class(es)	
TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	N.A.
Special precautions in connection with transport or conveyance	
Rail (RID):	3
TDG Special provisions:	59,142
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. Regulatory information

Safety, health and environmental regulations specific for the product in question
This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.
NPRI - National Pollutant Release Inventory
Substance(s) listed under NPRI:
None.
DSL inventory - Domestic substances list
no substances listed
NDSL inventory - Not Domestic substances list
no substances listed
TSCA inventory

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

All the components are listed on the TSCA inventory.

TSCA listed substances:

Hexamethylene diisocyanate, oligomers (biuret type) is listed in TSCA Section 8b
n-butyl acetate is listed in TSCA Section 8b
xylene [4] is listed in TSCA Section 8b
ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR
hexamethylene-di-isocyanate is listed in TSCA Section 8b, Section 8d HSDR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: n-butyl acetate, xylene [4], ethylbenzene, hexamethylene-di-isocyanate.
Section 313 – Toxic chemical list: xylene [4], ethylbenzene, hexamethylene-di-isocyanate.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds
xylene [4] - Reportable quantity: 100 pounds
ethylbenzene - Reportable quantity: 1000 pounds
hexamethylene-di-isocyanate - Reportable quantity: 100 pounds.
Reportable quantity for mixture: 1562.5 pounds.

CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111
xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
hexamethylene-di-isocyanate is listed in CAA Section 112(b) - HAP.

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 304, Section 311
xylene [4] is listed in CWA Section 304, Section 311
ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:
ethylbenzene - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:
n-butyl acetate
xylene [4]
ethylbenzene
hexamethylene-di-isocyanate.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:
n-butyl acetate
xylene [4]
ethylbenzene
hexamethylene-di-isocyanate.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:
n-butyl acetate
xylene [4]
ethylbenzene.

Volatile Organic compounds - VOCs = 52.00 %

Volatile Organic compounds - VOCs = 520.00 g/l

Volatile CMR substances = 0.02 %

Organic Carbon - C = 0.34

16. Other information

Full text of phrases referred to in Section 3:

H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

LCB057/1

Page n. 9 of 10

Safety Data Sheet

LCB057 CATALIZZATORE non ingiallente- non-yellowing catalyst

H225 Highly flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H330 Fatal if inhaled.
H302 Harmful if swallowed.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Safety Data Sheet dated 4/4/2018, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average