

Heavy-Duty Casters Roulettes pour usage robuste

Mold-On Polyurethane on Cast Iron Polyuréthane moulé sur acier



F25106



F25206



F25006

FEATURES AND APPLICATIONS

- Quiet, soft and cushioned non-marking ride, ideal on hard surface floors
- Polyurethane tread molded on cast iron hub; performs well in extreme operating temperatures
- Resists oil and chemical absorption
- Lubrication fittings for swivel raceway and wheel bearings
- Heavy-duty fork and wide tread width contribute to added load rating

CARACTÉRISTIQUES ET APPLICATIONS

- Roulement silencieux, souple et en douceur qui ne marque pas les planchers, parfait pour les planchers à surface dure
- Bande de roulement en polyuréthane moulé sur jante d'acier; performant bien par températures extrêmes
- Résistantes à l'absorption de produits chimiques et pétroliers
- Chemin de roulement pivotant et roulement de roue dotés de graisseurs
- Chape robuste et largeur de bande augmentée pour une capacité de charge accrue

		A		B	C	D	E x F	See / Voir : page 36
No.	TYPE			TREAD WIDTH LARGEUR DE BANDE	TOTAL HEIGHT HAUTEUR TOTALE	OFFSET DISTANCE DISTANCE DE DÉPORT	PLATE SIZE DIMENSION DE PLAQUE	WEIGHT POIDS
N F25104	Swivel / Pivot	4" / 100 mm	441 lb / 200 kg	2" / 50 mm	5-15/32" / 139 mm	1-11/32" / 34 mm	4" x 4-17/32" 102 x 115 mm	4.8 lb 2.18 kg
N F25204	Swivel + brake Pivot + frein	4" / 100 mm	441 lb / 200 kg	2" / 50 mm	5-15/32" / 139 mm	1-11/32" / 34 mm	4" x 4-17/32" 102 x 115 mm	5.4 lb 2.45 kg
N F25004	Rigid / Fixe	4" / 100 mm	441 lb / 200 kg	2" / 50 mm	5-15/32" / 139 mm		4" x 4-17/32" 102 x 115 mm	4.4 lb 2 kg
N F25105	Swivel / Pivot	5" / 125 mm	551 lb / 250 kg	2" / 50 mm	6-1/2" / 165 mm	1-17/32" / 39 mm	4" x 4-17/32" 102 x 115 mm	6 lb 2.72 kg
N F25205	Swivel + brake Pivot + frein	5" / 125 mm	551 lb / 250 kg	2" / 50 mm	6-1/2" / 165 mm	1-17/32" / 39 mm	4" x 4-17/32" 102 x 115 mm	6.18 lb 2.8 kg
N F25005	Rigid / Fixe	5" / 125 mm	551 lb / 250 kg	2" / 50 mm	6-1/2" / 165 mm		4" x 4-17/32" 102 x 115 mm	4.9 lb 2.22 kg
N F25106	Swivel / Pivot	6" / 150 mm	661 lb / 300 kg	2" / 50 mm	7-5/16" / 186 mm	1-11/16" / 43 mm	4" x 4-17/32" 102 x 115 mm	6.7 lb 3.04 kg
N F25206	Swivel + brake Pivot + frein	6" / 150 mm	661 lb / 300 kg	2" / 50 mm	7-5/16" / 186 mm	1-11/16" / 43 mm	4" x 4-17/32" 102 x 115 mm	7.12 lb 3.23 kg
N F25006	Rigid / Fixe	6" / 150 mm	661 lb / 300 kg	2" / 50 mm	7-5/16" / 186 mm		4" x 4-17/32" 102 x 115 mm	5.8 lb 2.63 kg
N F25108	Swivel / Pivot	8" / 200 mm	772 lb / 350 kg	2" / 50 mm	9-9/32" / 236 mm	2-1/8" / 54 mm	4" x 4-17/32" 102 x 115 mm	8.6 lb 3.9 kg
N F25208	Swivel + brake Pivot + frein	8" / 200 mm	772 lb / 350 kg	2" / 50 mm	9-9/32" / 236 mm	2-1/8" / 54 mm	4" x 4-17/32" 102 x 115 mm	9.24 lb 4.19 kg
N F25008	Rigid / Fixe	8" / 200 mm	772 lb / 350 kg	2" / 50 mm	9-9/32" / 236 mm		4" x 4-17/32" 102 x 115 mm	8 lb 3.63 kg