

Safety Data Sheet



LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

Safety Data Sheet dated 1/25/2019, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: MAKOLOR EXTRA Arancio universale - Orange universal stain

Other means of identification:

Trade code: LAM004

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Dye

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Competent person responsible for the safety data sheet:

msds@sivam.it




Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Warning, Eye Irrit. 2A, Causes serious eye irritation.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.
Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... Thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor/... if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	/ 1
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	B

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH No.: 01-2119457435-35	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 20% - < 25%	Acid Orange 139	CAS: 72275-69-5 EC: 276-558-6 REACH No.: 01-2120119369-52	⚠ US-HAE/C2 Aquatic Chronic 2 H411
>= 15% - < 20%	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	Index number: 603-096-00-8 CAS: 112-34-5 EC: 203-961-6 REACH No.: 01-2119475104-44	⚠ A.3/2A Eye Irrit. 2A H319

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin
ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
- 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
EU - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm
ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

DNEL Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
Worker Industry: 553.5 mg/m³ - Worker Professional: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 369 mg/m³ - Worker Professional: 369 mg/m³ - Consumer: 43.9 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 183 mg/kg - Worker Professional: 183 mg/kg - Consumer: 78 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 33 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
Worker Industry: 101.2 mg/m³ - Worker Professional: 101.2 mg/m³ - Consumer: 60.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 67.5 mg/m³ - Worker Professional: 67.5 mg/m³ - Consumer: 40.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 83 mg/kg - Worker Professional: 83 mg/kg - Consumer: 50 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
Target: Fresh Water - Value: 10 mg/l
Target: Marine water - Value: 1 mg/l
Target: Intermittent emission - Value: 100 mg/l
Target: Freshwater sediments - Value: 52.3 mg/kg
Target: Marine water sediments - Value: 5.2 mg/kg
Target: Soil (agricultural) - Value: 4.59 mg/kg
Target: Microorganisms in sewage treatments - Value: 100 mg/l
- 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
Target: Fresh Water - Value: 1.1 mg/l
Target: Marine water - Value: 0.11 mg/l
Target: Freshwater sediments - Value: 4.4 mg/kg
Target: Marine water sediments - Value: 0.44 mg/kg
Target: Microorganisms in sewage treatments - Value: 200 mg/l
Target: Soil (agricultural) - Value: 0.32 mg/kg
Target: Food chain - Value: 56 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	coloured fluid
Odour:	typical
Odour threshold:	N.D.
pH:	8
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	100 - 228 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.D.

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

Vapour density:	> 1
Flash point:	> 30 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	1.010 - 1.030
Solubility in water:	soluble
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

MAKOLOR EXTRA Arancio universale - Orange universal stain

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

d) respiratory or skin sensitisation

Not classified

No data available for the product

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

No data available for the product

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) acute toxicity:

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg
 Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 54.6 mg/l - Duration: 4h
 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
 a) acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat = 2410 mg/kg - Source: OCSE 401
 Test: LD50 - Route: Skin - Species: Rabbit = 2764 mg/kg - Source: OCSE 402

Substance(s) listed on the NTP report on Carcinogens:
 None.

Substance(s) listed on the IARC Monographs:
 None.

Substance(s) listed as OSHA Carcinogen(s):
 None.

Substance(s) listed as NIOSH Carcinogen(s):
 None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

MAKOLOR EXTRA Arancio universale - Orange universal stain

The product is classified: Aquatic Chronic 3 - H412

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia > 21100 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 4600 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae > 1000 mg/l - Notes: 7 d

Persistence and degradability

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 96 - Notes: OECD 301E

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 90 - Notes: OECD TG 301 C

Bioaccumulative potential

N.A.

Mobility in soil

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Mobility in soil: Mobile

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number

ADR-UN Number: 1263

DOT number: UN1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL

DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound

IATA-Shipping Name: PAINT RELATED MATERIAL

IMDG-Shipping Name: PAINT RELATED MATERIAL

Transport hazard class(es)

ADR-Class: 3

DOT Hazard Class: 3

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

ADR - Hazard identification number:	30
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	III
DOT Packing group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions	
Rail (RID):	3
DOT Special provisions:	367, B1, B52, B131, IB3, T2, TP1, TP29
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 650
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-Ems:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in TSCA Section 8b, Section 8d HSDR

Acid Orange 139 is listed in TSCA Section 8b

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 – Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in CAA Section 112(b) - HON

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON,

Section 112(b) - HAP.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

1-methoxy-2-propanol; monopropylene glycol methyl ether.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

1-methoxy-2-propanol; monopropylene glycol methyl ether.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

1-methoxy-2-propanol; monopropylene glycol methyl ether.

Volatile Organic compounds - VOCs = 68.00 %

LAM004/1

Page n. 7 of 8

Safety Data Sheet

LAM004 MAKOLOR EXTRA Arancio universale - Orange universal stain

Volatile Organic compounds - VOCs = 693.60 g/l

Volatile CMR substances = 0.10 %

Organic Carbon - C = 0.37

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H319 Causes serious eye irritation.

Safety Data Sheet dated 1/25/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average