

Safety Data Sheet



LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Safety Data Sheet dated 5/7/2018, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name:

SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Other means of identification

Trade code:

LFA247

Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... Thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water/...
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/ doctor/ if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see ... On this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	B.6/3 Flam. Liq. 3 H226 A.1/4/Dermal Acute Tox. 4 H312 A.1/4/Inhal Acute Tox. 4 H332 A.2/2 Skin Irrit. 2 H315 A.8/3 STOT SE 3 H335 A.9/2 STOT RE 2 H373 A.10/1 Asp. Tox. 1 H304
>= 5% - < 7%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	B.6/2 Flam. Liq. 2 H225 CAN-HAE/C3 Aquatic Chronic 3 H412 A.1/4/Inhal Acute Tox. 4 H332 A.9/2 STOT RE 2 H373 A.10/1 Asp. Tox. 1 H304
>= 5% - < 7%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	B.6/2 Flam. Liq. 2 H225 A.8/3 STOT SE 3 H336
>= 3% - < 5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	B.6/3 Flam. Liq. 3 H226 A.8/3 STOT SE 3 H336
>= 1% - < 3%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	B.6/2 Flam. Liq. 2 H225 A.10/1 Asp. Tox. 1 H304 A.2/2 Skin Irrit. 2 H315 A.7/2 Unst. Expl. A.8/3 STOT SE 3 H336

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

			 A.9/2 STOT RE 2 H373
>= 1% - < 3%	ethyl acetate	Index number: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH No.: 01-2119475103-46	 B.6/2 Flam. Liq. 2 H225  A.3/2A Eye Irrit. 2A H319  A.8/3 STOT SE 3 H336

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

isobutyl acetate [2] - CAS: 110-19-0

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

ethyl acetate - CAS: 141-78-6

ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr
EU - TWA(8h): 734 mg/m³, 200 ppm - STEL: 1468 mg/m³, 400 ppm

DNEL Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human
Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal
- Frequency: Long Term, systemic effects
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4

Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation
- Frequency: Long Term, systemic effects
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0

Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 300 mg/m³ - Exposure: Human
Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4

Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human
Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human
Inhalation - Frequency: Short Term, local effects
Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, local effects

toluene - CAS: 108-88-3

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethyl acetate - CAS: 141-78-6

Worker Industry: 1468 mg/m³ - Worker Professional: 1468 mg/m³ - Consumer: 734 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 1468 mg/m³ - Worker Professional: 1468 mg/m³ - Consumer: 734 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 63 mg/kg - Worker Professional: 63 mg/kg - Consumer: 37 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 734 mg/m³ - Worker Professional: 734 mg/m³ - Consumer: 367 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 734 mg/m³ - Worker Professional: 734 mg/m³ - Consumer: 367 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 4.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.32 mg/l

Target: Marine water - Value: 0.32 mg/l

Target: Intermittent emission - Value: 0.32 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Freshwater sediments - Value: 13.7 mg/kg

Target: Soil (agricultural) - Value: 2.68 mg/kg

Target: Intermittent emission - Value: 0.1 mg/l

Target: Microorganisms in sewage treatments - Value: 9.6 mg/l

isobutyl acetate [2] - CAS: 110-19-0

Target: Fresh Water - Value: 0.17 mg/l

Target: Marine water - Value: 0.017 mg/l

Target: Intermittent emission - Value: 0.34 mg/l

Target: Microorganisms in sewage treatments - Value: 200 mg/l

Target: Freshwater sediments - Value: 0.877 mg/kg

Target: Marine water sediments - Value: 0.0877 mg/kg

Target: Soil (agricultural) - Value: 0.0755 mg/kg

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Intermittent emission - Value: 0.36 mg/l

Target: Freshwater sediments - Value: 0.98 mg/kg

Target: Marine water sediments - Value: 0.098 mg/kg

Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

Target: Soil (agricultural) - Value: 0.09 mg/kg

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l

Target: Marine water - Value: 0.68 mg/l

Target: Intermittent emission - Value: 0.68 mg/l

Target: Freshwater sediments - Value: 16.39 mg/kg

Target: Marine water sediments - Value: 16.39 mg/kg

Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

Target: Soil (agricultural) - Value: 2.89 mg/kg

ethyl acetate - CAS: 141-78-6

Target: Fresh Water - Value: 0.24 mg/l

Target: Marine water - Value: 0.024 mg/l

Target: Intermittent emission - Value: 1.65 mg/l

Target: Microorganisms in sewage treatments - Value: 650 mg/l

Target: Freshwater sediments - Value: 1.15 mg/kg

Target: Marine water sediments - Value: 0.115 mg/kg

Target: Soil (agricultural) - Value: 0.148 mg/kg

Target: Food chain - Value: 200 mg/kg

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Eye protection:
Eye glasses with side protection. (EN166)

Protection for skin:
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:
Use respiratory protection where ventilation is insufficient or exposure is prolonged.
Use adequate protective respiratory equipment.

Thermal Hazards:
None

9. Physical and chemical properties

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	< 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.990 - 1.010
Solubility in water:	N.D.
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity
It may generate dangerous reactions (See subsections below)

Chemical stability
It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions
It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid
Avoid accumulating electrostatic charge.

Incompatible materials
Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products
None.

11. Toxicological information

Information on toxicological effects
Toxicological information of the product:
SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

- a) acute toxicity
Not classified
No data available for the product
- b) skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
The product is classified: Eye Irrit. 2A H319
- d) respiratory or skin sensitisation
Not classified
No data available for the product
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

- g) reproductive toxicity
The product is classified: Repr. 2 H361
- h) STOT-single exposure
The product is classified: STOT SE 3 H335
- i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
 Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401
 Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg
 Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403
 Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423
 Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403
 Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4934 mg/kg - Source: OCSE 401
 Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation. Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

toluene - CAS: 108-88-3

Effects following acute exposure:

At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.

At 400 ppm: worsening of symptoms and mental confusion.

ethyl acetate - CAS: 141-78-6

The product is extremely volatile and provokes for inhalation, irritation to respiratory tracts. Acute exposition can cause depression of central nervous system with effects such as drowsiness, reflex loss, narcosis.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

ethylbenzene - Group 2B

toluene - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

LFA247/1

Page n. 7 of 11

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

Not classified for environmental hazards

No data available for the product

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 2.4 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 4.6 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Duration h: 168

isobutyl acetate [2] - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 397 mg/l - Duration h: 72 - Notes: OCSE 201

Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202

Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Algae > 100 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 165 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 230 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 2.4 mg/l - Notes: 21d

Persistence and degradability

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 70-80 - Notes: N.A.

isobutyl acetate [2] - CAS: 110-19-0

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

14. Transport information



UN number	
TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint
Transport hazard class(es)	
TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	N.A.
Special precautions in connection with transport or conveyance	
Rail (RID):	3
TDG Special provisions:	59,142
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. Regulatory information

Safety, health and environmental regulations specific for the product in question
 This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.
 NPRI - National Pollutant Release Inventory
 Substance(s) listed under NPRI:
 None.
 DSL inventory - Domestic substances list
 no substances listed

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

NDSL inventory - Not Domestic substances list
no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b
ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR
isobutyl acetate [2] is listed in TSCA Section 8b
n-butyl acetate is listed in TSCA Section 8b
toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR
ethyl acetate is listed in TSCA Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, isobutyl acetate [2], n-butyl acetate, toluene, ethyl acetate.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene, toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds

ethyl acetate - Reportable quantity: 5000 pounds.

Reportable quantity for mixture: 354.4779426 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

n-butyl acetate is listed in CAA Section 111

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethyl acetate is listed in CAA Section 111.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

isobutyl acetate [2] is listed in CWA Section 311

n-butyl acetate is listed in CWA Section 304, Section 311

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

ethyl acetate is listed in CWA Section 304.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

ethylbenzene - Listed as carcinogen

toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

n-butyl acetate

toluene

ethyl acetate.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

n-butyl acetate

toluene

ethyl acetate.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

Safety Data Sheet

LFA247 SIVOSAT 5 Finitura PU trasparente - Clear PU top coat 5 gloss

n-butyl acetate
toluene
ethyl acetate.

Volatile Organic compounds - VOCs = 48.86 %
Volatile Organic compounds - VOCs = 493.49 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.40

16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H336 May cause drowsiness or dizziness.
H319 Causes serious eye irritation.

Safety Data Sheet dated 5/7/2018, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average