

## Safety Data Sheet



# LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Safety Data Sheet dated 11/13/2019, version 1

## 1. Identification

### GHS Product identifier

Mixture identification:

Trade name:

CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Other means of identification

Trade code:

LXC908

### Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Converter for paints

### Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel : +1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel : +1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

### Competent person responsible for the safety data sheet:

msds@sivam.it

### Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

## 2. Hazard identification

### Classification of the hazardous product

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

### GHS label elements, including precautionary statements

#### Hazard pictograms:



#### Danger

#### Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.



## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

|                     |                                                                          | 29                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| >= 0.5% -<br>< 1.5% | cyclohexanone                                                            | Index number: 606-010-00-7<br>CAS: 108-94-1<br>EC: 203-631-1<br>REACH No.: 01-2119453616-35 | <div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.1/4/Oral Acute Tox. 4 H302</div> </div> <div> <div></div> <div>A.1/4/Dermal Acute Tox. 4 H312</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.3/1 Eye Dam. 1 H318</div> </div> <div> <div></div> <div>A.1/4/Inhal Acute Tox. 4 H332</div> </div> |
| >= 0.1% -<br>< 1%   | toluene                                                                  | Index number: 601-021-00-3<br>CAS: 108-88-3<br>EC: 203-625-9<br>REACH No.: 01-2119471310-51 | <div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.7/2 Repr. 2 H361</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>                            |
| >= 0.1% -<br>< 1%   | Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) | CAS: 147900-93-4                                                                            | <div> <div></div> <div>A.1/4/Oral Acute Tox. 4 H302</div> </div> <div> <div></div> <div>CAN-HAE/C2 Aquatic Chronic 2 H411</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.4.2/1A Skin Sens. 1A H317</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div>                                                             |
| 900 ppm             | Fatty acids, tall-oil, compds. with oleylamine                           | CAS: 85711-55-3<br>EC: 288-315-1<br>REACH No.: 01-2119974148-28                             | <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.3/1 Eye Dam. 1 H318</div> </div> <div> <div></div> <div>A.4.2/1A Skin Sens. 1A H317</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div>                                                                                                                                          |
| 10 ppm              | Decamethylcyclopentasiloxane (D5)                                        | CAS: 541-02-6<br>EC: 208-764-9<br>REACH No.: 01-2119511367-43                               | The product is not classified as dangerous according to WHMIS 2015.                                                                                                                                                                                                                                                                                                                      |
| 10 ppm              | octamethylcyclotetrasiloxane (D4)                                        | Index number: 014-018-00-1<br>CAS: 556-67-2<br>EC: 209-136-7<br>REACH No.: 01-2119529238-36 | <div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.7/2 Repr. 2 H361</div> </div> <div> <div></div> <div>CAN-HAE/C4 Aquatic Chronic 4 H413</div> </div>                                                                                                                                                                                                 |

The actual concentration of the components listed above is withheld as a trade secret.

The actual concentration of the components listed above is withheld as a trade secret.

#### 4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### 5. Fire-fighting measures

LXC908/1

Page n. 3 of 13

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Suitable and unsuitable extinguishing media  
Suitable extinguishing media:  
In case of fire: Use ... to extinguish.  
Unsuitable extinguishing media:  
None in particular.  
Specific hazards arising from the hazardous product  
Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.  
Hazardous combustion products:  
None  
Explosive properties: N.D. in volume  
Oxidizing properties: N.D.  
Special protective equipment and precautions for fire-fighters  
Use suitable breathing apparatus .  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures  
Wear personal protection equipment.  
Remove all sources of ignition.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Provide adequate ventilation.  
Use appropriate respiratory protection.  
See protective measures under point 7 and 8.  
Methods and material for containment and cleaning up  
Wash with plenty of water.

---

#### 7. Handling and storage

Precautions for safe handling  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Exercise the greatest care when handling or opening the container.  
Do not use on extensive surface areas in premises where there are occupants.  
Use localized ventilation system.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
See also section 8 for recommended protective equipment.  
Advice on general occupational hygiene:  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
Conditions for safe storage, including any incompatibilities  
Always keep in a well ventilated place.  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Avoid accumulating electrostatic charge.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.  
Safety electric system.  
Storage temperature:  
Store at ambient temperature.

---

#### 8. Exposure controls/personal protection

Control parameters  
xylene [4] - CAS: 1330-20-7  
EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair  
ethylbenzene - CAS: 100-41-4  
EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin  
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair  
isobutyl acetate [2] - CAS: 110-19-0  
ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr  
n-butyl acetate - CAS: 123-86-4  
ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

cyclohexanone - CAS: 108-94-1  
 EU - TWA(8h): 40.8 mg/m<sup>3</sup>, 10 ppm - STEL: 81.6 mg/m<sup>3</sup>, 20 ppm - Notes: Skin  
 ACGIH - TWA(8h): 20 ppm - STEL: 50 ppm - Notes: Skin, A3 - Eye and URT irr

toluene - CAS: 108-88-3  
 EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
 ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

Decamethylcyclpentasiloxane (D5) - CAS: 541-02-6  
 ACGIH - TWA(8h): 10 ppm

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 ACGIH - TWA(8h): 123 mg/m<sup>3</sup>, 10 ppm

**DNEL Exposure Limit Values**

xylene [4] - CAS: 1330-20-7  
 Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal  
 - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 15 mg/m<sup>3</sup> - Exposure: Human Inhalation  
 - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0  
 Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg - Exposure: Human Dermal -  
 Frequency: Long Term, systemic effects  
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, local effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, local effects

cyclohexanone - CAS: 108-94-1  
 Worker Industry: 4 mg/kg - Worker Professional: 4 mg/kg - Consumer: 1 mg/kg - Exposure: Human Dermal -  
 Frequency: Long Term, systemic effects  
 Worker Industry: 40 mg/m<sup>3</sup> - Worker Professional: 40 mg/m<sup>3</sup> - Consumer: 10 mg/m<sup>3</sup> - Exposure: Human Inhalation  
 - Frequency: Long Term, systemic effects  
 Consumer: 1.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

toluene - CAS: 108-88-3  
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal  
 - Frequency: Long Term, systemic effects  
 Worker Industry: 192 mg/m<sup>3</sup> - Worker Professional: 192 mg/m<sup>3</sup> - Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Worker Industry: 73 mg/m<sup>3</sup> - Worker Professional: 73 mg/m<sup>3</sup> - Consumer: 13 mg/m<sup>3</sup> - Exposure: Human Inhalation  
 - Frequency: Long Term, systemic effects  
 Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg - Exposure: Human Inhalation -  
 Frequency: Short Term, systemic effects  
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects  
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

**PNEC Exposure Limit Values**

xylene [4] - CAS: 1330-20-7  
 Target: Fresh Water - Value: 0.327 mg/l  
 Target: Marine water - Value: 0.327 mg/l  
 Target: Intermittent emission - Value: 0.327 mg/l  
 Target: Freshwater sediments - Value: 12.46 mg/kg  
 Target: Marine water sediments - Value: 12.46 mg/kg

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

|                                                                                                                               |                                                                 |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  |
|                                                                                                                               | Target: Soil (agricultural) - Value: 2.31 mg/kg                 |
| ethylbenzene - CAS: 100-41-4                                                                                                  |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.1 mg/l                           |
|                                                                                                                               | Target: Marine water - Value: 0.01 mg/l                         |
|                                                                                                                               | Target: Freshwater sediments - Value: 13.7 mg/kg                |
|                                                                                                                               | Target: Soil (agricultural) - Value: 2.68 mg/kg                 |
|                                                                                                                               | Target: Intermittent emission - Value: 0.1 mg/l                 |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  |
| isobutyl acetate [2] - CAS: 110-19-0                                                                                          |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.17 mg/l                          |
|                                                                                                                               | Target: Marine water - Value: 0.017 mg/l                        |
|                                                                                                                               | Target: Intermittent emission - Value: 0.34 mg/l                |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 200 mg/l   |
|                                                                                                                               | Target: Freshwater sediments - Value: 0.877 mg/kg               |
|                                                                                                                               | Target: Marine water sediments - Value: 0.0877 mg/kg            |
|                                                                                                                               | Target: Soil (agricultural) - Value: 0.0755 mg/kg               |
| n-butyl acetate - CAS: 123-86-4                                                                                               |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.18 mg/l                          |
|                                                                                                                               | Target: Marine water - Value: 0.018 mg/l                        |
|                                                                                                                               | Target: Intermittent emission - Value: 0.36 mg/l                |
|                                                                                                                               | Target: Freshwater sediments - Value: 0.98 mg/kg                |
|                                                                                                                               | Target: Marine water sediments - Value: 0.098 mg/kg             |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 35.6 mg/l  |
|                                                                                                                               | Target: Soil (agricultural) - Value: 0.09 mg/kg                 |
| cyclohexanone - CAS: 108-94-1                                                                                                 |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.033 mg/l                         |
|                                                                                                                               | Target: Marine water - Value: 0.0033 mg/l                       |
|                                                                                                                               | Target: Freshwater sediments - Value: 0.168 mg/kg               |
|                                                                                                                               | Target: Marine water sediments - Value: 0.017 mg/kg             |
|                                                                                                                               | Target: Intermittent emission - Value: 0.329 mg/l               |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 10 mg/l    |
|                                                                                                                               | Target: Soil (agricultural) - Value: 0.014 mg/kg                |
| toluene - CAS: 108-88-3                                                                                                       |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.68 mg/l                          |
|                                                                                                                               | Target: Marine water - Value: 0.68 mg/l                         |
|                                                                                                                               | Target: Intermittent emission - Value: 0.68 mg/l                |
|                                                                                                                               | Target: Freshwater sediments - Value: 16.39 mg/kg               |
|                                                                                                                               | Target: Marine water sediments - Value: 16.39 mg/kg             |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 13.61 mg/l |
|                                                                                                                               | Target: Soil (agricultural) - Value: 2.89 mg/kg                 |
| octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2                                                                             |                                                                 |
|                                                                                                                               | Target: Fresh Water - Value: 0.00044 mg/l                       |
|                                                                                                                               | Target: Marine water - Value: 0.00044 mg/l                      |
|                                                                                                                               | Target: Freshwater sediments - Value: 0.128 mg/kg               |
|                                                                                                                               | Target: Marine water sediments - Value: 0.013 mg/kg             |
|                                                                                                                               | Target: Microorganisms in sewage treatments - Value: 100 mg/kg  |
|                                                                                                                               | Target: Soil (agricultural) - Value: 0.136 mg/kg                |
| Biological Exposure Index                                                                                                     |                                                                 |
| xylene [4] - CAS: 1330-20-7                                                                                                   |                                                                 |
| Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn           |                                                                 |
| ethylbenzene - CAS: 100-41-4                                                                                                  |                                                                 |
| Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and acid fenilgliossalico -             |                                                                 |
| Sampling Period: End of turn; End of working week                                                                             |                                                                 |
| toluene - CAS: 108-88-3                                                                                                       |                                                                 |
| Value: 0.02 mg/L - medium: Blood - Biological Indicator: Toluene in blood - Sampling Period: End of turn; End of working week |                                                                 |
| Appropriate engineering controls                                                                                              |                                                                 |
| None                                                                                                                          |                                                                 |
| Individual protection measures, such as personal protective equipment (PPE)                                                   |                                                                 |
| Eye protection:                                                                                                               |                                                                 |
| Eye glasses with side protection. (EN166)                                                                                     |                                                                 |
| Protection for skin:                                                                                                          |                                                                 |
| Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.                           |                                                                 |
| Protection for hands:                                                                                                         |                                                                 |
| Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)                        |                                                                 |
| Respiratory protection:                                                                                                       |                                                                 |
| Use respiratory protection where ventilation is insufficient or exposure is prolonged.                                        |                                                                 |

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Use adequate protective respiratory equipment.  
Thermal Hazards:  
None

---

#### 9. Physical and chemical properties

|                                               |                           |
|-----------------------------------------------|---------------------------|
| Appearance and colour:                        | opalescent fluid          |
| Odour:                                        | typical                   |
| Odour threshold:                              | N.D.                      |
| pH:                                           | N.A.                      |
| Melting point / freezing point:               | N.D. °C                   |
| Initial boiling point and boiling range:      | > 110 °C                  |
| Flash point:                                  | < 23 °C                   |
| Evaporation rate:                             | N.D.                      |
| Solid/gas flammability:                       | N.A.                      |
| Upper/lower flammability or explosive limits: | 7.0% - 0.9% Vol. (Xylene) |
| Vapour pressure:                              | N.D. (20 °C)              |
| Vapour density:                               | > 1                       |
| Relative density:                             | 0.970 - 1.000             |
| Solubility in water:                          | N.D.                      |
| Solubility in oil:                            | partial                   |
| Partition coefficient (n-octanol/water):      | N.D.                      |
| Auto-ignition temperature:                    | > 300 °C                  |
| Decomposition temperature:                    | N.D. °C                   |
| Viscosity:                                    | N.D.                      |

---

#### 10. Stability and reactivity

Reactivity  
It may generate dangerous reactions (See subsections below)

Chemical stability  
It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions  
It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid  
Avoid accumulating electrostatic charge.

Incompatible materials  
Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products  
None.

---

#### 11. Toxicological information

Information on toxicological effects  
Toxicological information of the product:  
CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

- a) acute toxicity  
Not classified  
No data available for the product
- b) skin corrosion/irritation  
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation  
The product is classified: Eye Irrit. 2A H319
- d) respiratory or skin sensitisation  
The product is classified: Skin Sens. 1A H317
- e) germ cell mutagenicity  
Not classified  
No data available for the product
- f) carcinogenicity  
Not classified  
No data available for the product
- g) reproductive toxicity  
The product is classified: Repr. 2 H361
- h) STOT-single exposure  
The product is classified: STOT SE 3 H335
- i) STOT-repeated exposure  
The product is classified: STOT RE 2 H373
- j) aspiration hazard

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 27.12 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat = 17.6 mg/l - Duration: 1h

i) STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

cyclohexanone - CAS: 108-94-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1890 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 794 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 6.2 ml/l - Duration: 4h

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 1570 mg/kg

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 g/kg - Source: OECD 423

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

cyclohexanone - CAS: 108-94-1

The product is harmful if inhaled.

Repeated exposure can cause burning and irritation to eyes, mouth, nose and throat, cough, respiratory impairment, dizziness, cephalgia, nausea and vomiting.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

ethylbenzene - Group 2B

cyclohexanone - Group 3

toluene - Group 3.

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

## 12. Ecological information

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

Not classified for environmental hazards

No data available for the product

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day

Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96

isobutyl acetate [2] - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 397 mg/l - Duration h: 72 - Notes: OCSE 201

Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202

Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

cyclohexanone - CAS: 108-94-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72

Endpoint: EC50 - Species: Fish = 527 mg/l - Duration h: 96

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 15.2 mg/l - Duration h: 48 - Notes: OECD TG 202

Endpoint: EC50 - Species: Algae = 7.4 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203

### Persistence and degradability

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80

isobutyl acetate [2] - CAS: 110-19-0

Biodegradability: Readily biodegradable

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

toluene - CAS: 108-88-3  
 Biodegradability: Readily biodegradable  
 Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4  
 Biodegradability: Non-readily biodegradable  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310  
 Bioaccumulative potential  
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 Bioaccumulation: Bioaccumulative  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Bioaccumulation: Bioaccumulative  
 Mobility in soil  
 N.A.  
 Other adverse effects  
 None

### 13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### 14. Transport information



UN number  
 TDG number: UN1263  
 ADR-UN Number: 1263  
 DOT number: UN1263  
 IATA-UN Number: 1263  
 IMDG-UN Number: 1263  
 UN proper shipping name  
 TDG-Shipping Name: PAINT  
 ADR-Shipping Name: PAINT  
 DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound  
 IATA-Shipping Name: PAINT  
 IMDG-Shipping Name: PAINT  
 Transport hazard class(es)  
 TDG Class: 3  
 ADR-Class: 3  
 DOT Hazard Class: 3  
 ADR - Hazard identification number: 33  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3  
 Packing group  
 TDG Packing group: II  
 ADR-Packing Group: II  
 DOT Packing group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II  
 Environmental hazards  
 ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No  
 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
 N.A.  
 Special precautions in connection with transport or conveyance  
 Rail (RID): 3  
 TDG Special provisions: 59,142  
 DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28  
 DOT Labels: 3

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

|                                                   |                  |
|---------------------------------------------------|------------------|
| ADR-Subsidiary hazards:                           | -                |
| ADR-S.P.:                                         | 163 367 640D 650 |
| ADR-Transport category (Tunnel restriction code): | 2 (D/E)          |
| IATA-Passenger Aircraft:                          | 353              |
| IATA-Subsidiary hazards:                          | -                |
| IATA-Cargo Aircraft:                              | 364              |
| IATA-S.P.:                                        | A3 A72 A192      |
| IATA-ERG:                                         | 3L               |
| IMDG-EmS:                                         | F-E , S-E        |
| IMDG-Subsidiary hazards:                          | -                |
| IMDG-Stowage and handling:                        | Category B       |
| IMDG-Segregation:                                 | -                |

## 15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

xylene [4] is listed in NPRI Part 5

ethylbenzene is listed in NPRI Part 1, Group A

n-butyl acetate is listed in NPRI Part 5

toluene is listed in NPRI Part 5.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

isobutyl acetate [2] is listed in TSCA Section 8b

n-butyl acetate is listed in TSCA Section 8b

cyclohexanone is listed in TSCA Section 8b, Section 8d HSDR

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) is listed in TSCA Section 8b

Fatty acids, tall-oil, compds. with oleylamine is listed in TSCA Section 8b

Decamethylcyclotetrasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, isobutyl acetate [2], n-butyl acetate, cyclohexanone, toluene.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene, toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds

cyclohexanone - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 236.0383326 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

n-butyl acetate is listed in CAA Section 111

cyclohexanone is listed in CAA Section 111, Section 112(b) - HON

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

isobutyl acetate [2] is listed in CWA Section 311  
n-butyl acetate is listed in CWA Section 304, Section 311  
toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

#### USA - State specific regulations

##### California Proposition 65

Substance(s) listed under California Proposition 65:  
ethylbenzene - Listed as carcinogen  
toluene - Listed as reproductive toxicant.

##### Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:  
xylene [4]  
ethylbenzene  
isobutyl acetate [2]  
n-butyl acetate  
cyclohexanone  
toluene.

##### New Jersey Right to know

Substance(s) listed under New Jersey Right to know:  
xylene [4]  
ethylbenzene  
isobutyl acetate [2]  
n-butyl acetate  
cyclohexanone  
toluene.

##### Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:  
xylene [4]  
ethylbenzene  
isobutyl acetate [2]  
n-butyl acetate  
cyclohexanone  
toluene.

Volatile Organic compounds - VOCs = 56.10 %  
Volatile Organic compounds - VOCs = 560.97 g/l  
Volatile CMR substances = 0.00 %  
Organic Carbon - C = 0.49

---

## 16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
H225 Highly flammable liquid and vapour.  
H412 Harmful to aquatic life with long lasting effects.  
H336 May cause drowsiness or dizziness.  
H302 Harmful if swallowed.  
H318 Causes serious eye damage.  
H361 Suspected of damaging fertility or the unborn child.  
H411 Toxic to aquatic life with long lasting effects.  
H317 May cause an allergic skin reaction.  
H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 11/13/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ATE: Acute Toxicity Estimate

## Safety Data Sheet

### LXC908 CONVERTER PU per CHROMOSAT 80- CONV PU for CHROMOSAT 80

|           |                                                                                     |
|-----------|-------------------------------------------------------------------------------------|
| ATEmix:   | Acute toxicity Estimate (Mixtures)                                                  |
| CAS:      | Chemical Abstracts Service (division of the American Chemical Society).             |
| CLP:      | Classification, Labeling, Packaging.                                                |
| DNEL:     | Derived No Effect Level.                                                            |
| EINECS:   | European Inventory of Existing Commercial Chemical Substances.                      |
| GHS:      | Globally Harmonized System of Classification and Labeling of Chemicals.             |
| HMIS:     | Hazardous Materials Identification System                                           |
| IARC:     | International Agency for Research on Cancer                                         |
| IATA:     | International Air Transport Association.                                            |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO:     | International Civil Aviation Organization.                                          |
| ICAO-TI:  | Technical Instructions by the "International Civil Aviation Organization" (ICAO).   |
| IMDG:     | International Maritime Code for Dangerous Goods.                                    |
| INCI:     | International Nomenclature of Cosmetic Ingredients.                                 |
| KSt:      | Explosion coefficient.                                                              |
| LC50:     | Lethal concentration, for 50 percent of test population.                            |
| LD50:     | Lethal dose, for 50 percent of test population.                                     |
| NFPA:     | National Fire Protection Association                                                |
| NIOSH:    | National Institute for Occupational Safety and Health                               |
| NTP:      | National Toxicology Program                                                         |
| OSHA:     | Occupational Safety and Health Administration.                                      |
| PNEC:     | Predicted No Effect Concentration.                                                  |
| RID:      | Regulation Concerning the International Transport of Dangerous Goods by Rail.       |
| STEL:     | Short Term Exposure limit.                                                          |
| STOT:     | Specific Target Organ Toxicity.                                                     |
| TLV:      | Threshold Limiting Value.                                                           |
| TWA:      | Time-weighted average                                                               |