

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

Safety Data Sheet dated 7/4/2019, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name:

IDROFIX- polivalente trasp.-10- opaco

Other means of identification:

Trade code:

LWM055

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel: +1-860-529-7704

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel: +1-860-529-7704

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).

Label elements

The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:


None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

HEALTH	/ 0
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number	Classification
>= 0.1% - < 0.25%	ammonia ...%	Index number: 007-001-01-2 CAS: 1336-21-6 EC: 215-647-6 REACH No.: 01-2119982985-14	A.2/1B Skin Corr. 1B H314 A.8/3 STOT SE 3 H335 US-HAE/A1 Aquatic Acute 1 H400
5 ppm	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: 613-167-00-5 CAS: 55965-84-9	A.2/1B Skin Corr. 1B H314 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Inhal Acute Tox. 3 H331
2 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH No.: 01-2120761540-60	A.2/2 Skin Irrit. 2 H315 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 A.1/4/Oral Acute Tox. 4 H302
560 ppb	2-metil-2H-isotiazol-3-one	CAS: 2682-20-4 EC: 220-239-6 REACH No.: 01-2120764690-50	A.1/2/Inhal Acute Tox. 2 H330 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

Treatment:

None

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

ammonia ...% - CAS: 1336-21-6

ACGIH - TWA: 18 mg/m³, 25 ppm - STEL: 27 mg/m³, 35 ppm

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

TLV TWA - 0,05 mg/m³

TLV STEL - 0,23 mg/m³

DNEL Exposure Limit Values

ammonia ...% - CAS: 1336-21-6

Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 47.6 mg/m³ - Worker Professional: 47.6 mg/m³ - Consumer: 23.8 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 47.6 mg/m³ - Worker Professional: 47.6 mg/m³ - Consumer: 23.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 36 mg/m³ - Worker Professional: 36 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 14 mg/m³ - Worker Professional: 14 mg/m³ - Consumer: 2.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

ammonia ...% - CAS: 1336-21-6

Target: Fresh Water - Value: 0.0011 mg/l

Target: Marine water - Value: 0.0011 mg/l

Target: Intermittent emission - Value: 0.0068 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable gloves type:(EN374)

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	8.5
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 100 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.D.
Vapour density:	> 1
Flash point:	N.A.
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	1.010 - 1.030
Solubility in water:	miscible
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

IDROFIX- polivalente trasp.-10- opaco

a) acute toxicity

Not classified

No data available for the product

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

- b) skin corrosion/irritation
Not classified
No data available for the product
- c) serious eye damage/irritation
Not classified
No data available for the product
- d) respiratory or skin sensitisation
Not classified
No data available for the product
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
Not classified
No data available for the product
- h) STOT-single exposure
Not classified
No data available for the product
- i) STOT-repeated exposure
Not classified
No data available for the product
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h

Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg

2-metil-2H-isotiazol-3-one - CAS: 2682-20-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

IDROFIX- polivalente trasp.-10- opaco

Not classified for environmental hazards

No data available for the product

ammonia ...% - CAS: 1336-21-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96

Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

- b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201
 - Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211
 - Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210
- 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
 - a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
 - Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
 - b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
 - Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
- 2-metil-2H-isotiazol-3-one - CAS: 2682-20-4
 - a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96
 - Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48
- Persistence and degradability
 - 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
 - Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B
- Bioaccumulative potential
 - N.A.
- Mobility in soil
 - N.A.
- Other adverse effects
 - None

13. DISPOSAL CONSIDERATIONS

- Waste treatment and disposal methods
 - Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

- UN number
 - Not classified as dangerous in the meaning of transport regulations.
- UN proper shipping name
 - N.A.
- Transport hazard class(es)
 - N.A.
- Packing group
 - N.A.
- Environmental hazards
 - ADR-Environmental Pollutant: No
 - IMDG-Marine pollutant: No
- Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
 - N.A.
- Special precautions
 - N.A.

15. REGULATORY INFORMATION

- USA - Federal regulations
 - TSCA - Toxic Substances Control Act
 - TSCA inventory: all the components are listed on the TSCA inventory.
 - TSCA listed substances:
 - ammonia ...% is listed in TSCA Section 8b
 - mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b
 - 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b
 - 2-metil-2H-isotiazol-3-one is listed in TSCA Section 12b, Section 8b.
 - SARA - Superfund Amendments and Reauthorization Act
 - Section 302 – Extremely Hazardous Substances: no substances listed.
 - Section 304 – Hazardous substances: ammonia ...%.
 - Section 313 – Toxic chemical list: ammonia ...%.
 - CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 - Substance(s) listed under CERCLA: ammonia ...% - Reportable quantity: 1000 pounds.
 - Reportable quantity for mixture: 693481.276 pounds.

Safety Data Sheet

LWM055 IDROFIX- polivalente trasp.-10- opaco

CAA - Clean Air Act
CAA listed substances:
None.
CWA - Clean Water Act
CWA listed substances:
ammonia ...% is listed in CWA Section 311.

USA - State specific regulations
California Proposition 65
Substance(s) listed under California Proposition 65:
None.
Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
ammonia ...%.
New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
ammonia ...%.
Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
ammonia ...%.

Volatile Organic compounds - VOCs = 3.90 %
Volatile Organic compounds - VOCs = 40.16 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.02

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H315 Causes skin irritation.
H302 Harmful if swallowed.
H330 Fatal if inhaled.

Safety Data Sheet dated 7/4/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.
This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.

LWM055/1

Page n. 7 of 8

Safety Data Sheet

.

LWM055 IDROFIX- polivalente trasp.-10- opaco

PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average