Safety Data Sheet

LWM000 SIVAWOOD Effetto naturale all'acqua - Clear WB for Natural Effect

Safety Data Sheet dated 5/23/2019, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name: SIVAWOOD Effetto naturale all'acqua - Clear WB for Natural Effect

Other means of identification

Trade code: LWM000

Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

The product is not classified as dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements

The product is not classified as dangerous according to WHMIS 2015.

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 1% - < 5%	2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	Index number: 603-014-00-0 CAS: 111-76-2 EC: 203-905-0 REACH No.: 01-2119475108-36	A.2/2 Skin Irrit. 2 H315 A.3/2A Eye Irrit. 2A H319 B.6/4 Flam. Liq. 4 H227 A.1/4/Oral Acute Tox. 4 H302 A.1/4/Dermal Acute Tox. 4 H312 A.1/4/Inhal Acute Tox. 4 H332
10 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH No.: 01-2120761540-60	A.2/2 Skin Irrit. 2 H315 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 A.1/4/Oral Acute Tox. 4 H302
364 ppb	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: 613-167-00-5 CAS: 55965-84-9	A.2/1B Skin Corr. 1B H314 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Inhal Acute Tox. 3 H331

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not use on extensive surface areas in premises where there are occupants.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
Storage temperature:
Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

EU - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

TLV TWA - 0,05 mg/m3
TLV STEL - 0,23 mg/m3

DNEL Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Worker Industry: 125 mg/kg - Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 98 mg/m3 - Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l
Target: Marine water - Value: 0.88 mg/l
Target: Intermittent emission - Value: 9.1 mg/l
Target: Freshwater sediments - Value: 8.14 mg/kg
Target: Marine water sediments - Value: 3.46 mg/kg
Target: Microorganisms in sewage treatments - Value: 463 mg/l
Target: Food chain - Value: 20 mg/kg
Target: Soil (agricultural) - Value: 2.33 mg/kg

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable gloves type:(EN374)

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.

pH:	8.5
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 100 °C
Flash point:	N.A.
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.D.
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	1.010 - 1.030
Solubility in water:	miscible
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity
Stable under normal conditions
Chemical stability
Stable under normal conditions
Possibility of hazardous reactions
None
Conditions to avoid
Stable under normal conditions.
Incompatible materials
None in particular.
Hazardous decomposition products
None.

11. Toxicological information

Information on toxicological effects
Toxicological information of the product:
SIVAWOOD Effetto naturale all'acqua - Clear WB for Natural Effect
a) acute toxicity
Not classified
No data available for the product
b) skin corrosion/irritation
Not classified
No data available for the product
c) serious eye damage/irritation
Not classified
No data available for the product
d) respiratory or skin sensitisation
Not classified
No data available for the product
e) germ cell mutagenicity
Not classified
No data available for the product
f) carcinogenicity
Not classified
No data available for the product
g) reproductive toxicity
Not classified
No data available for the product
h) STOT-single exposure
Not classified
No data available for the product
i) STOT-repeated exposure
Not classified
No data available for the product
j) aspiration hazard
Not classified
No data available for the product
Toxicological information of the main substances found in the product:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 1300 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 523 Ppm - Duration: 4h
Test: LC50 - Route: Skin - Species: Rabbit > 435 mg/kg
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg
Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h
Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
The product is harmful if inaled,swallowed or absorbed through skin.Repeated or extended exposures cause headache,drowsiness,weakness, stuttering,blurred vision,urinary albumin,kidneys demages,liver enlargement and haemolysis.

Substance(s) listed on the NTP report on Carcinogens:
None.
Substance(s) listed on the IARC Monographs:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3.
Substance(s) listed as OSHA Carcinogen(s):
None.
Substance(s) listed as NIOSH Carcinogen(s):
None.

12. Ecological information

Ecotoxicity
Adopt good working practices, so that the product is not released into the environment.
SIVAWOOD Effetto naturale all'acqua - Clear WB for Natural Effect
Not classified for environmental hazards
No data available for the product
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Algae = 623 mg/l - Duration h: 72 - Notes: OECD 201
Endpoint: EC50 - Species: Daphnia = 1550 mg/l - Duration h: 48 - Notes: OECD 202
Endpoint: LC50 - Species: Fish = 1474 mg/l - Duration h: 96 - Notes: OECD 203
b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 d
Endpoint: NOEC - Species: Algae = 62.5 mg/l - Duration h: 72
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72
Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48
Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96
b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201
Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211
Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210
Persistence and degradability
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
Biodegradability: Readily biodegradable - Duration h: 28 days - %: 90.4 - Notes: OECD 301B
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B
Bioaccumulative potential
N.A.

Mobility in soil
N.A.
Other adverse effects
None

13. Disposal considerations

Safe handling and methods for disposal
Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number
Not classified as dangerous in the meaning of transport regulations.
UN proper shipping name
N.A.
Transport hazard class(es)
N.A.
Packing group
N.A.
Environmental hazards
ADR-Enviromental Pollutant: No
IMDG-Marine pollutant: No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
N.A.
Special precautions in connection with transport or conveyance
N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question
This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.
NPRI - National Pollutant Release Inventory
Substance(s) listed under NPRI:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in NPRI Part 5.
DSL inventory - Domestic substances list
All the components are listed in the DSL..
NDSL inventory - Not Domestic substances list
no substances listed
TSCA inventory
All the components are listed on the TSCA inventory.
TSCA listed substances:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 8b, Section 8d HSDR
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b.

USA - Federal regulations
SARA - Superfund Amendments and Reauthorization Act
Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: no substances listed.
Section 313 – Toxic chemical list: no substances listed.
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
No substances listed.
CAA - Clean Air Act
CAA listed substances:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in CAA Section 111.
CWA - Clean Water Act
CWA listed substances:
None.

USA - State specific regulations
California Proposition 65
Substance(s) listed under California Proposition 65:
None.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Volatile Organic compounds - VOCs = 3.82 %
Volatile Organic compounds - VOCs = 39.34 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.02

16. Other information

Full text of phrases referred to in Section 3:
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H227 Combustible liquid.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.
H314 Causes severe skin burns and eye damage.
H410 Very toxic to aquatic life with long lasting effects.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.

Safety Data Sheet dated 5/23/2019, version 1
Disclaimer:
The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.
This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average