

Safety Data Sheet



LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Safety Data Sheet dated 9/19/2022, version 2

1. Identification

GHS Product identifier
Mixture identification:
Trade name: CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU
Other means of identification
Trade code: LXC908
Recommended use and restrictions on use
Recommended use:
IS- Industrial use
PW - Professional use
Converter for paints
Supplier's details
Company:
NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02-903041
Importer:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-800-361-6000
Emergency phone number for Canada: Canutec (613) 996-6666
Distributor:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-800-361-6000
Emergency phone number for Canada: Canutec (613) 996-6666
Competent person responsible for the safety data sheet:
msds@sivam.it
Emergency phone number
NUOVA S.I.V.A.M. SpA - Tel. +39 02- 903041 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. Hazard identification

Classification of the hazardous product
 ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
 ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
 ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
 ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
 ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
 ⚠ Warning, STOT SE 3, May cause respiratory irritation.
 ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
 Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

GHS label elements, including precautionary statements

Hazard pictograms:



Danger

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash ... Thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/ doctor/if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see ... On this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use ... to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

LXC908/2

Page n. 2 of 17

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Qty	Name	Ident. Number	Classification
>= 30% - < 60%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	⚠ B.6/3 Flam. Liq. 3 H226 CAN-HAE/C3 Aquatic Chronic 3 H412 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>=5% - < 10%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304 CAN-HAE/C3 Aquatic Chronic 3 H412
>= 1% - < 5%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H336
>= 0.5% - < 1.5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 0.5% - < 1.5%	cyclohexanone	Index number: 606-010-00-7 CAS: 108-94-1 EC: 203-631-1 REACH No.: 01-2119453616-35	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.1/4/Oral Acute Tox. 4 H302 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.1/4/Inhal Acute Tox. 4 H332
>= 0.1% - < 1%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.7/2 Repr. 2 H361 ⚠ A.10/1 Asp. Tox. 1 H304 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.8/3 STOT SE 3 H336
>= 0.1% - < 1%	Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z)	CAS: 147900-93-4 REACH No.: 01-2119971821-33	⚠ A.1/4/Oral Acute Tox. 4 H302 ⚠ CAN-HAE/C2 Aquatic Chronic 2 H411 ⚠ A.2/2 Skin Irrit. 2 H315

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

			⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
900 ppm	Fatty acids, tall-oil, compds. with oleylamine	CAS: 85711-55-3 EC: 288-315-1 REACH No.: 01-2119974148-28	⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
11 ppm	Decamethylcyclopentasiloxane (D5)	CAS: 541-02-6 EC: 208-764-9 REACH No.: 01-2119511367-43	The product is not classified as dangerous according to WHMIS 2015.
11 ppm	octamethylcyclotetrasiloxane (D4)	Index number: 014-018-00-1 CAS: 556-67-2 EC: 209-136-7 REACH No.: 01-2119529238-36	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.7/2 Repr. 2 H361 CAN-HAE/C4 Aquatic Chronic 4 H413

The actual concentration of the components listed above is withheld as a trade secret.

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do NOT induce vomiting.

In case of Inhalation:

- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

- In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

- In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

- None in particular.

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

xylylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

isobutyl acetate [2] - CAS: 110-19-0

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

cyclohexanone - CAS: 108-94-1

EU - TWA(8h): 40.8 mg/m³, 10 ppm - STEL: 81.6 mg/m³, 20 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - STEL: 50 ppm - Notes: Skin, A3, BEI - Eye and URT irr

toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

ACGIH - TWA(8h): 10 ppm

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

ACGIH - TWA(8h): 123 mg/m³, 10 ppm

DNEL Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³

- Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4

Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0

Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³

- Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 300 mg/m³

- Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4

Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³

- Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³

- Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 11 mg/kg - Worker Professional: 11 mg/kg - Consumer: 6 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

cyclohexanone - CAS: 108-94-1

Worker Industry: 4 mg/kg - Worker Professional: 4 mg/kg - Consumer: 1 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Worker Industry: 40 mg/m³ - Worker Professional: 40 mg/m³ - Consumer: 10 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

toluene - CAS: 108-88-3
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 Worker Industry: 0.024 mg/kg - Worker Professional: 0.024 mg/kg - Consumer: 0.012 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Worker Industry: 24.2 mg/m³ - Worker Professional: 24.2 mg/m³ - Consumer: 4.3 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 97.3 mg/m³ - Worker Professional: 97.3 mg/m³ - Consumer: 17.3 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Worker Industry: 73 mg/m³ - Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -
 Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

xylylene [4] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Marine water - Value: 0.327 mg/l
 Target: Intermittent emission - Value: 0.327 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg
 Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil (agricultural) - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4
 Target: Fresh Water - Value: 0.1 mg/l
 Target: Marine water - Value: 0.01 mg/l
 Target: Freshwater sediments - Value: 13.7 mg/kg
 Target: Marine water sediments - Value: 1.37 mg/kg
 Target: Intermittent emission - Value: 0.1 mg/l
 Target: Microorganisms in sewage treatments - Value: 9.6 mg/l
 Target: Soil (agricultural) - Value: 2.68 mg/kg

isobutyl acetate [2] - CAS: 110-19-0
 Target: Fresh Water - Value: 0.17 mg/l
 Target: Marine water - Value: 0.017 mg/l
 Target: Intermittent emission - Value: 0.34 mg/l
 Target: Microorganisms in sewage treatments - Value: 200 mg/l
 Target: Freshwater sediments - Value: 0.877 mg/kg
 Target: Marine water sediments - Value: 0.0877 mg/kg
 Target: Soil (agricultural) - Value: 0.0755 mg/kg

n-butyl acetate - CAS: 123-86-4
 Target: Fresh Water - Value: 0.18 mg/l
 Target: Marine water - Value: 0.018 mg/l
 Target: Intermittent emission - Value: 0.36 mg/l
 Target: Freshwater sediments - Value: 0.98 mg/kg

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Target: Marine water sediments - Value: 0.098 mg/kg
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l
 Target: Soil (agricultural) - Value: 0.09 mg/kg
 cyclohexanone - CAS: 108-94-1
 Target: Fresh Water - Value: 0.033 mg/l
 Target: Marine water - Value: 0.0033 mg/l
 Target: Freshwater sediments - Value: 0.168 mg/kg
 Target: Marine water sediments - Value: 0.017 mg/kg
 Target: Intermittent emission - Value: 0.329 mg/l
 Target: Microorganisms in sewage treatments - Value: 10 mg/l
 Target: Soil (agricultural) - Value: 0.014 mg/kg
 toluene - CAS: 108-88-3
 Target: Fresh Water - Value: 0.074 mg/l
 Target: Marine water - Value: 0.0074 mg/l
 Target: Freshwater sediments - Value: 1.78 mg/kg
 Target: Marine water sediments - Value: 0.178 mg/kg
 Target: Microorganisms in sewage treatments - Value: 0.84 mg/l
 Target: Soil (agricultural) - Value: 0.313 mg/kg
 Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 Target: Fresh Water - Value: 0.006 mg/l
 Target: Marine water - Value: 0.0006 mg/l
 Target: Freshwater sediments - Value: 2.46 mg/kg
 Target: Marine water sediments - Value: 0.25 mg/kg
 Target: Soil (agricultural) - Value: 0.28 mg/kg
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Target: Fresh Water - Value: 0.0012 mg/kg
 Target: Marine water - Value: 0.00012 mg/kg
 Target: Freshwater sediments - Value: 11 mg/kg
 Target: Marine water sediments - Value: 1.1 mg/kg
 Target: Microorganisms in sewage treatments - Value: 10 mg/l
 Target: Soil (agricultural) - Value: 2.54 mg/kg
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Target: Fresh Water - Value: 0.00044 mg/l
 Target: Marine water - Value: 0.000044 mg/l
 Target: Freshwater sediments - Value: 0.128 mg/kg
 Target: Marine water sediments - Value: 0.013 mg/kg
 Target: Microorganisms in sewage treatments - Value: 10 mg/kg
 Target: Soil (agricultural) - Value: 0.136 mg/kg
 Biological Exposure Index
 xylene [4] - CAS: 1330-20-7
 Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine -
 Sampling Period: End of turn
 ethylbenzene - CAS: 100-41-4
 Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and
 acid fenilgliossalico - Sampling Period: End of turn; End of working week
 toluene - CAS: 108-88-3
 Value: 0.02 mg/L - medium: Blood - Biological Indicator: Toluene in blood - Sampling
 Period: End of turn; End of working week
 Appropriate engineering controls
 None
 Individual protection measures, such as personal protective equipment (PPE)
 Eye protection:
 Eye glasses with side protection. (EN166)
 Protection for skin:
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or
 viton.

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.
Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour:	Liquid, opalescent
Odour:	typical
Odour threshold:	N.D.
pH:	Not Relevant
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	< 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.970 - 1.000
Solubility in water:	N.D.
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

- d) respiratory or skin sensitisation
The product is classified: Skin Sens. 1A H317
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
The product is classified: Repr. 2 H361
- h) STOT-single exposure
The product is classified: STOT SE 3 H335
- i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
- Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h
- Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg
- Test: LD50 - Route: Inhalation - Species: Rat = 17.2 mg/l - Duration: 1h

i) STOT-repeated exposure:

- Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401
- Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg
- Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403
- Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 10760 mg/kg - Source: OECD 423
- Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h - Source: OECD 403
- Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

cyclohexanone - CAS: 108-94-1

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 1890 mg/kg
- Test: LD50 - Route: Skin - Species: Rabbit > 794 mg/kg
- Test: LC50 - Route: Inhalation - Species: Rat > 6.2 ml/l - Duration: 4h

toluene - CAS: 108-88-3

a) acute toxicity:

- Test: LD50 - Route: Oral - Species: Rat = 5000 mg/kg
- Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
- Test: LC50 - Route: Inhalation - Species: Rat = 25.7 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:

- Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 1570 mg/kg

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD 423

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

cyclohexanone - CAS: 108-94-1

The product is harmful if inhaled.

Repeated exposure can cause burning and irritation to eyes, mouth, nose and throat, cough, respiratory impairment, dizziness, cephalgia, nausea and vomiting.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

ethylbenzene - Group 2B

cyclohexanone - Group 3

toluene - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

The product is classified: Aquatic Chronic 3 - H412

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

- b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day
 - Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96
- isobutyl acetate [2] - CAS: 110-19-0
 - a) Aquatic acute toxicity:
 - Endpoint: EC50 - Species: Algae = 370 mg/l - Duration h: 72 - Notes: OCSE 201
 - Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202
 - Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203
 - b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)
- n-butyl acetate - CAS: 123-86-4
 - a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203
 - Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72
 - b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Algae = 200 mg/l - Duration h: 72
- cyclohexanone - CAS: 108-94-1
 - a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72
 - Endpoint: EC50 - Species: Fish = 527 mg/l - Duration h: 96
- toluene - CAS: 108-88-3
 - a) Aquatic acute toxicity:
 - Endpoint: EC50 - Species: Algae = 12.5 mg/l - Duration h: 72
 - Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48
 - Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96
 - b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72
 - Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d
 - Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 - a) Aquatic acute toxicity:
 - Endpoint: EC50 - Species: Algae = 7.89 mg/l - Duration h: 72 - Notes: OECD 201
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
 - a) Aquatic acute toxicity:
 - Endpoint: EC50 - Species: Daphnia = 15.2 mg/l - Duration h: 48 - Notes: OECD TG 202
 - Endpoint: EC50 - Species: Algae = 7.43 mg/l - Duration h: 72 - Notes: OECD TG 201
 - Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203
- Persistence and degradability
 - xylylene [4] - CAS: 1330-20-7
 - Biodegradability: Readily biodegradable
 - ethylbenzene - CAS: 100-41-4
 - Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80
 - isobutyl acetate [2] - CAS: 110-19-0
 - Biodegradability: Readily biodegradable
 - n-butyl acetate - CAS: 123-86-4
 - Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83
 - toluene - CAS: 108-88-3
 - Biodegradability: Readily biodegradable
 - Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 - Biodegradability: Non-readily biodegradable
 - Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
 - Biodegradability: Readily biodegradable
 - Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 - Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

310
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310
 Bioaccumulative potential
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Bioaccumulation: Bioaccumulative
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Bioaccumulation: Bioaccumulative
 Mobility in soil
 N.A.
 Other adverse effects
 None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information



UN number

TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263

UN proper shipping name

TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
IATA-Shipping Name:	PAINT
IMDG-Shipping Name:	PAINT

Transport hazard class(es)

TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3

Packing group

TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II

Environmental hazards

ADR-Environmental Pollutant:	No
------------------------------	----

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

IMDG-Marine pollutant: No
 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) N.A.
 Special precautions in connection with transport or conveyance
 Rail (RID): 3
 TDG Special provisions: 59,142
 DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
 DOT Labels: 3
 ADR-Subsidiary hazards: -
 ADR-S.P.: 163 367 640D 650
 ADR-Transport category (Tunnel restriction code): 2 (D/E)
 IATA-Passenger Aircraft: 353
 IATA-Subsidiary hazards: -
 IATA-Cargo Aircraft: 364
 IATA-S.P.: A3 A72 A192
 IATA-ERG: 3L
 IMDG-Ems: F-E , S-E
 IMDG-Subsidiary hazards: -
 IMDG-Stowage and handling: Category B
 IMDG-Segregation: -

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

xylene [4] is listed in NPRI Part 5

ethylbenzene is listed in NPRI Part 1, Group A

n-butyl acetate is listed in NPRI Part 5

toluene is listed in NPRI Part 5.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

isobutyl acetate [2] is listed in TSCA Section 8b

n-butyl acetate is listed in TSCA Section 8b

cyclohexanone is listed in TSCA Section 8b, Section 8d HSDR

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) is listed in TSCA Section 8b

Fatty acids, tall-oil, compds. with oleylamine is listed in TSCA Section 8b

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, isobutyl acetate [2],

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

n-butyl acetate, cyclohexanone, toluene.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene, toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds

cyclohexanone - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 236.0717658 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

n-butyl acetate is listed in CAA Section 111

cyclohexanone is listed in CAA Section 111, Section 112(b) - HON

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

isobutyl acetate [2] is listed in CWA Section 311

n-butyl acetate is listed in CWA Section 304, Section 311

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

ethylbenzene - Listed as carcinogen

toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

n-butyl acetate

cyclohexanone

toluene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

n-butyl acetate

cyclohexanone

toluene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

xylene [4]

ethylbenzene

isobutyl acetate [2]

n-butyl acetate

cyclohexanone

toluene.

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

Volatile Organic compounds - VOCs = 56.10 %
Volatile Organic compounds - VOCs = 560.98 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.49

16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H302 Harmful if swallowed.
H318 Causes serious eye damage.
H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 9/19/2022, version 2
Sections modified from the previous revision:

- 2. Hazard identification
- 3. Composition/Information on ingredients
- 8. Exposure controls/personal protection
- 9. Physical and chemical properties
- 11. Toxicological information
- 12. Ecological information
- 14. Transport information
- 15. Regulatory information

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS: Hazardous Materials Identification System

Safety Data Sheet

LXC908 CONV per PU CHROMOLACK TIX 80- CHROMOLACK TIX CONV for matt PU

IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average