



unit: INCH

| | | | |
|---------------------------------|--------------------|----|-------|
| L LENGHT TOLERANCE | ≤5/8" | +0 | -0,03 |
| | >5/8" to ≤1-1/2" | +0 | -0,05 |
| | >1-1/2" to ≤2-3/4" | +0 | -0,06 |

| | | |
|--------------------|------|-------------|
| S THREAD | < 1" | Full Thread |
| | ≥ 1" | 2/3 Thread |

| SCREW | M PUNCH | | Q DRIVE DEPTH | A HEAD DIAM. | E BODY DIAM. | D THREAD DIAM. | THREAD PER INCH | TORK INCH/ POUND |
|-------|------------|-----|------------------|-----------------|-----------------|-------------------|--------------------|---------------------|
| # 6 | # 2 | Min | 0,048 | 0,244 | 0,103 | 0,142 | 12 | 24 |
| | | Max | 0,063 | 0,279 | 0,108 | 0,153 | | |
| # 7 | # 2 | Min | 0,048 | 0,268 | 0,112 | 0,159 | 11 | 30 |
| | | Max | 0,063 | 0,305 | 0,117 | 0,166 | | |

Flat countersunk head, Quadrex recessed #2, Coarse thread, Zinc

Date: 5 septembre 2013

Fait par: PB