
THE ONE BOX SOLUTION
FOR CYLINDRICAL AND MORTISE LOCKS

The 4100

Key Features:

- Use with cylindrical locksets, mortise locks without dead bolts and mortise exit devices.
- 1 - 3/8" shallow backset allows the 4100 to be used in 2" fire rated frames with 1/2" sheetrock ingress.
- **Flexible:** Always be prepared!
  - 4 faceplates included
  - 12 & 24DC, 12-24 AC
  - 2 Trim Skirts Provided (32D Finish)
  - Regular and Torx® Screws
- **Strong:** Exceeds 3,250 lbs. of Holding Force
- **Durable:** Exceeds 1,000,000 Life Cycles
- Works with the Schlage® L Series & Yale® 8700 Series without relocating mounting tabs.



Standards:

- **WH** recognized **3-hour fire rated – UL10C**, Fire Tests of Door Assemblies.
- BHMA Grade 1: ANSI/BHMA A156.5
- **UBC 7-2**, Uniform building Code.
- **CAN4 S104**, Standard Method for Fire Tests of Door Assemblies.
- **NFPA 252** - Issue: 1999/01/01 Standard Methods of Fire Tests of Door Assemblies.

NOTE: WH fire listing is void when using fail safe action.



All Four Faceplates and Premium Trim Skirts included



