Trines 1000 Series Electric Strikes

Light Commercial Strikes

00 Series
01 Series
2000 Series
1000 Series

1000 Series Features:

- Durability - 500,000 Life Cycles.
- Releases Under Slight Door Pre-Load.
- Holding Force - 1000 lbs.
- Tall Latch Cavity.
- Non Handed Operation.
- Screw Terminals - Quick Connection.

1000 Series Electrical Characteristics:

Voltage	Amps	Ohms (Ω)	Duty	Sound
6-14VAC	0.495 - 1.090	8.5	Intermittent.	Buzz
6-14VDC	0.650 - 1.240	8.5	Continuous.	Silent
16-24VAC	0.270 - 0.480	50.0	Intermittent.	Buzz
16-24VDC	0.380 - 0.610	50.0	Continuous.	Silent

1001-2
For use in new or replacement installations in wood and metal jambs. For use with locksets havir throw, based on 1/8” door gap.

Steel Face Plate 5-7/8” x 1-1/4” -- Narrow Style Face Plate -- Mortise Backset 1-1/2” -- Cavity De Cavity Width 9/16” -- Cavity Height 1-11/16”

Available Finishes: 1001-2 (Brass Powder Coated) -- 1001-2C (Satin Chrome or - BHMA652)

Downloadable content:

- **1001-2 Dimensions (PDF)**