11B Specifications

Case – Machined from solid extruded brass

Standard Finish – 626 satin chromium plated

Width – 1-5/8"

Length – 2-1/16"

Thickness – 25/32"

Shackle: The shackle locks at both heel and toe. The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

Material – Brass or stainless steel

Diamter – 1/4"

Width or opening – 7/8"

ASTM F883 – Meets Grade 3 with stainless steel shackle

ASTM 5883 – Meets Grade 6 for option E. (Corrosion resistance).



11B Padlock

11B72 11B722 11B772 11B782

How To Order – 11B

11B	7	2	T

Series	Core Housing	Shackle Height	Function Code	Chain Option	Special Stamp No.	Options
11B – brass 1/4" diameter	**7**– 7 pin housing accepts all BEST® cores	**Steel** **2** – 3/4" **22** –1-1/2" **72** – 2" **82** – 4" **Brass** **0** – 3/4" **20** –1-1/2" **70** – 2" **80** – 4"	**T** – key retained **L** – non-key retained	**M** – case drilled for clevis only **M1*** – bronze chain (available for brass padlocks only) **M5*** – galvanaized steel chain	**Blank** – BEST® logo **PS1010** – safety first Specify padlock stamp number or describe stamp. Price for speical stamps on request page 8	**F3** – rangible shackle (11B720 only) **606** – satin brass **ZZ** – double lockout page 8