www.sdcsecurity.com service@sdcsecurity.com
[t] 800.413.8783 805.494.0622 [f] 805.494.8861
801 Avenida Acaso, Camarillo CA 93012 • PO Box 3670, Camarillo CA 93011-3670

180 / 280 Series Surface Mount Bolt Locks

Universal Mounting Capability Provides Controlled Access of Doors, Closets and Cabinets.

The SDC universal surface mount electric bolt locks are available in failsafe and failsecure. The addition of a card reader, digital keypad or remote control provides access control and convenience of use for a variety of applications.



Applications

The SDC 180 and 280 series locks provide the ability to electronically secure several door configurations.

- Swinging or sliding doors
- Outswing or inswing doors
- Closet doors
- Pharmaceutical cabinets
- Gun cabinets
- Utility cabinets
- Museum display cases
- Retail display cases

Models

180ALIV	Surface mount, left hand, failsafe, with auto relock
180ARIV	Surface mount, right hand, failsafe, with auto relock
180ALRIV	Top Jamb, left hand reverse, failsafe, with auto relock
180ARRIV	Top Jamb, right hand reverse, failsafe, with auto relock
280LHV	Surface mount, left hand, or top jamb mount right hand reverse, failsecure less auto relock
280RHV	Surface mount, right hand, or top jamb mount, left hand reverse, failsecure less auto relock


Finish

V 628 Aluminum *(standard)*
Y 335 Black


Options

B	Bolt position sensor, SPDT
D	Door position sensor, SPDT
BR64XL	Rectifier for AC Operation

Installation



Surface Mount
Outswing Door



Top Jamb
Inswing or Sliding Door

Specifications

Lock Dimensions	6"L x 2"W x 2"H (152.4 x 50.8 x 50.8mm)
Bolt	Solid Stainless Steel 5/8" dia. x 1/2" throw (15.9 x 12.7mm)
Dual Voltage Coil	0.9 Amp @ 12VDC Continuous 0.45 Amp @ 24VDC Continuous

© 2012 Security Door Controls