ROCKWOOD®

ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions

2842- Automatic Flush Bolt Set



Available Finishes:

- US10BE/613E
- US32D/630
- US26D/626
- US26/625
- US10/612
- US10B/613
- US4/606
- US3/605

Specifications:

Material: Brass, stainless steel.

Fastener: 20 ea. #8 x 3/4 FH combo screws, 2 ea. #6 - 8 plastic anchors.
NOTE: No plastic anchor required for top only.

Features:
- Non-handed.
- Fully automatic–opening active door retracts top and bottom bolts.
- Low closing force.
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes.
- Bolt head rods are adjustable up to 1-1/2".
- Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- UL Listed.

Options: Can be used with the No. 570 Dust Proof Strike.

Other: For Metal Doors Fire Rated up to and Including 3 Hours, up to 4'w x 8'h

Size: 1" x 6-3/4"

Weight: 2.4 lbs.

ANSI A156.3: Type 25

Rockwood Manufacturing Company • 300 Main Street • Rockwood, PA 15557
P 800.458.2424 • F 800.922.9212 • info@rockwoodmfg.com • www.rockwoodmfg.com
Copyright © 2008 Rockwood Manufacturing Co. All rights reserved.