Architectural Door Accessories

ASSA ABLOY

The global leader in door opening solutions

Rockwood 2845 - Combination Flush Bolt Set



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

SIZE:
1" x 6 3/4"

WEIGHT:
2.4 lbs.

ANSI A156.3:
Type 27

Specifications:

MATERIAL:
Brass, Stainless Steel

FASTENERS:
18 ea. #8 x 3/4" Flat Head Combo Screws,
2 ea. #6 - 8 Plastic Anchors

FEATURES:

Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic–opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 1 1/2"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

300 Main Street
Rockwood, Pennsylvania 15557
P: 800.458.2424 • F: 800.922.9212
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.