ROCKWOOD®

ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions

2848- Automatic Flush Bolt with Bottom For Fire Rated Metal Doors Fire Bolt



Available Finishes:

- US10BE/613E
- US32D/630
- US26D/626
- US26/625
- US10/612
- US10B/613
- US4/606
- US3/605

Specifications:

Material: Brass, Stainless Steel

Fastener: 10 ea. #8 x 3/4 FH Combo Screws, 4 ea. Plastic Anchors

Features:
- Non-handed.
- Low (5 lbs. maximum) closing force.
- Fully automatic; opening active door retracts top bolt.
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike.
- Bolt head rod is adjustable up to 1-1/2".
- For fire rated metal doors labeled A, B, C, D, & E up to 4'w x 9'h.
- Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- Bottom fire bolt eliminates need for floor prep.
- Oversize fire bolt strike hole allows for slight door misalignment.
- UL Listed.

Top Bolt Size: 1" x 6-3/4"

Bottom Bolt Size: 13/16" dia.

Weight: 1.3 lbs.

Rockwood Manufacturing Company • 300 Main Street • Rockwood, PA 15557
P 800.458.2424 • F 800.922.9212 • info@rockwoodmfg.com • www.rockwoodmfg.com
Copyright © 2008 Rockwood Manufacturing Co. All rights reserved.