

Rockwood 2945 - Combination Flush Bolt Set



Specifications:

MATERIAL:

Brass, Stainless Steel

FASTENERS:

- 10 ea. #8 x $\frac{3}{4}$ " Flat Head Combo Screws
- 4 ea. #8-32 x $\frac{1}{2}$ " Flat Head Machine Screws
- 6 ea. #10 x 1" Flat Head Wood Screws
- 2 ea. #6-8 Plastic Anchors

FEATURES:

- For wood doors
- Can be used with the No. 570 Dust Proof Strike
- UL Listed

Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic—opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to $\frac{1}{2}$ "
- Thermal lock automatically locks the inactive door under high heat conditions due to fire



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

SIZE:

1" x 8 $\frac{1}{2}$ "

WEIGHT:

2.9 lbs.

ANSI A156.3:

Type 27