UL LISTED MAGLOCKS WITH DS

MAGLOCKS WITH ADJUSTABLE RELOCK TIME DELAY, LOCK STATUS SENSOR & DOOR STATUS SENSOR



PRIMARY APPLICATIONS





DESCRIPTION

BEA's UL Listed Maglock with DS provides a standards compliant locking solution for retail, healthcare, banking and other high security facilities that require a UL listed security product. UL Listed Maglocks can be used on hollow metal, wood, aluminum, glass and composite door materials.

The Maglock with DS is available in surface mount, single or double door configurations, with a holding force of 600 or 1,200 lbs. These locks include an adjustable 0-90 sec relock time delay, lock status sensor with visible LED and door status sensor.

FEATURES & BENEFITS

- UL Listed
- Adjustable 0-90 second relock time delay
- Lock Status Sensor with visible LED
- Door Status Sensor
- Input voltage of 12/24 VDC, must be used with UL Listed power supply
- Variety of mounting hardware available
- Available in access control packages with sensor, logic module, actuator and maglock

BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545
www.BEAinc.com

RELATED REQUEST TO EXIT PRODUCTS


R2E-100


FLY KIT


BR3 LOGIC MODULE



ACTUATORS


ELECTRIC STRIKES


POWER SUPPLIES

TECHNICAL SPECIFICATIONS

10MAGLOCK3ULDS

Door Configuration	Single, surface mount
Holding Force	600 lbs
Input Voltage	12/24 VDC (UL Listed power supply recommended)
Current Draw	.50 A @ 12 VDC .25 A @ 24 VDC
Dimensions	9.84 in x 1.65 in x 1.02 in
Relock Time Delay	0-90 s
Sensor	Lock Status Sensor, Door Status Sensor
Output Relay	Up to 1 A @ 24 VDC

10MAGLOCK6ULDS

Door Configuration	Double, surface mount
Holding Force	600 lbs
Input Voltage	12/24 VDC (UL Listed power supply recommended)
Current Draw	1 A @ 12 VDC .50 A @ 24 VDC
Dimensions	19.76 in x 1.65 in x 1.02 in
Relock Time Delay	0-90 s
Sensor	Lock Status Sensor, Door Status Sensor
Output Relay	Up to 1A @ 24 VDC

10MAGLOCK1ULDS

Door Configuration	Single, surface mount
Holding Force	1200 lbs
Input Voltage	12/24 VDC (UL Listed power supply recommended)
Current Draw	.50 A @ 12 VDC .30 A @ 24 VDC
Dimensions	10.47 in x 2.87 in x 1.58 in
Relock Time Delay	0-90 s
Sensor	Lock Status Sensor, Door Status Sensor
Output Relay	Up to 1 A @ 24 VDC

10MAGLOCK5ULDS

Door Configuration	Double, surface mount
Holding Force	1200 lbs
Input Voltage	12/24 VDC (UL Listed power supply recommended)
Current Draw	1 A @ 12 VDC .60 mA @ 24 VDC
Dimensions	20.94 in x 2.87 in x 1.58 in
Relock Time Delay	0-90 s
Sensor	Lock Status Sensor, Door Status Sensor
Output Relay	Up to 1 A @ 24 VDC


RELATED PRODUCTS



10MAGLOCK3ULDS
600 LB, SINGLE



10MAGLOCK6ULDS
600 LB, DOUBLE



10MAGLOCK1ULDS
1200 LB, SINGLE



10MAGLOCK5ULDS
1200 LB, DOUBLE



10LZBRMAG3UL
L & Z BRACKET
FOR 600 LB, SINGLE



10LZBRMAG1UL
L & Z BRACKET
FOR 1200 LB, SINGLE



10MAG6LZUL
(2) L & Z BRACKET
FOR 600 LB, DOUBLE



10MAG5LZUL
(2) L & Z BRACKET
FOR 1200 LB, DOUBLE


10UBRACKETUL
GLASS DOOR
MOUNTING KIT


10FILLER14UL
0.25 X 1.25 INCH
FILLER PLATE


10FILLER12UL
0.50 X 1.25 INCH
FILLER PLATE


10FILLER34UL
0.75 X 1.25 INCH
FILLER PLATE


10FILLER58UL
0.0625 X 0.0625 INCH
FILLER PLATE


10RIMHOUSING3UL
ARMATURE PLATE
HOUSING, 600 LB


10RIMHOUSING1UL
ARMATURE PLATE
HOUSING, 1200 LB


10SPACER3UL
VERTICAL SPACER
BRACKET, 600 LB


10SPACER1UL
VERTICAL SPACER
BRACKET, 1200 LB

© 2017 BEA, Inc. All rights reserved.

UL LISTED MAGLOCKS WITH DS

MAGLOCKS WITH ADJUSTABLE RELOCK TIME DELAY, LOCK STATUS SENSOR & DOOR STATUS SENSOR

BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545

79.0221.11 20161220