

# Electric Strikes

# 9400 Surface Mounted Electric Strike

*Works with rim exit devices up to 1/2" throw latchbolt*



## The slim-line, surface mounted solution.

The 9400 Series Electric Strike is a slim-line, surface mounted electric strike designed to accommodate rim exit devices with a 1/2" throw Pullman latchbolt. All components are completely encased within its 1/2" thick stainless steel housing, so no cutting on the frame is required for installation. Simply place the electric strike on the surface of the frame, align it with the exit latchbolt, and install.

An 1/8" spacer plate is provided to accommodate varying door gaps. The 9400 exceeds Grade 1 standards for strength and performance. It is field selectable for fail safe/fail secure operation, and for 12 or 24 VDC. The 9400 features a smooth cover to conceal the mounting screws and provide a sleek surface for superior looks.

## Features

### *Standard Features*

- Installs in metal and wood frames
- Wood screws not provided
- One 1/8" [3.2mm] spacer plate included
- Decorative cover for sleek look
- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs
- Dynamic strength 70 ft-lbs
- Endurance 1 million cycles
- Field selectable fail safe/fail secure
- Horizontal adjustability
- Non-handed
- Internally mounted solenoid
- Accommodates up to 1/2" [12.7mm] Pullman latch
- SecuriCare five-year, no-fault, no questions asked warranty *(Addition of SMART Pac® III extends the warranty to 10 years)*


### *Optional Features*

- **LBM** Latchbolt monitor
- **LBSM** Latchbolt strike monitor

### *Accessories*

- **9000-116-XXX** 1/16" Spacer plate (Available in 613E, 628E, 630 & BSP finishes)
- **9000-108-XXX** 1/8" Spacer plate (Available in 613E, 628E, 630 & BSP finishes)
- **9000-MTK** Metal template kit
- **SMB** Surface mounting box
- **2001M** Plug-in bridge rectifier
- **2004M** ElectroLynx® adapter
- **2005M3** SMART Pac® III
- **2006M** Plug-in buzzer
- **9000-ASB-XXX** Aluminum Spacer Bracket (availible 613E, 628E, 630 & BSP finis)
- **BN-250** 1/4-20 Blind Nuts




### *Spacer Plate Included*

The 9400 ships with one 1/8" [3.2mm] spacer plate included in the box. Units ordered in a 630 finish are stainless steel. All other finishave a black suede powder stainless steel spacer. Additional black spacer plates can be ordered as an accessory.

# 9400 Surface Mounted Electric Strike

## Specifications

### *Certifications*

- ANSI/BHMA A156.31, Grade 1
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 listed
- UL 305 listed
- RoHS compliant


### *Frame Application*

- Metal
- Wood

### *Electrical (DC Continuous Duty)*

- Dual voltage 12/24 VDC
- 450 mA at 12 VDC/250 mA at 24 VDC

## Dimensions




## How to Order

| SERIES | FINISH | OPTION (S) |
|---|---|---|
| 9400 | – 630 | – LBM |
| **9400** Surface-Mounted Electric Strike for 1/2" Pullman Rim Exit Devices; no faceplates required | **605** Bright Brass | **LBM** Latchbolt Monitor |
| | **606** Satin Brass | **LBSM** Latchbolt Strike Monitor |
| | **612** Satin Bronze | |
| | **613** Bronze Toned | |
| | **613E** Dark Oxidized Satin Bronze Powder | |
| | **629** Bright Stainless Steel | |
| | **630** Satin Stainless Steel | |
| | **BSP** Black Suede Powder | |

*NOTE: Electric strike compatibility is determined at time of electric strike product release. ASSA ABLOY is not responsible for incompatibility of products that have changed in design or craftsmanship by their respective manufacturers. When compatibility is a concern, contact Customer Support for application assistance.*



*Updated 9/28/22* Patent pending and/or patent www.assaabloydss.com/patents
Copyright © 2022, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Hanchett Entry Systems, Inc. is prohibited.