ALLEGION™


SCHLAGE
Portable security and cabinet locks
SAFE SHOES FOR P.E.
UNSAFE SHOES FOR P.E.
EXIT

Cabinet locks with cylinder

Cabinet deadbolt locks



CL100PB

Cylinder formats:
CL100PB - Conventional format

Interchangeable Core formats:
CL777R - Full Size IC (FSIC)
CL721G - Small Format IC (SFIC)

Rekeying: Release mechanism allows Conventional cylinder replacement. Interchangeable cores replaced using control key

Certifications: ANSI 156.11 - Conventional Grade 1; FSIC and SFIC Grade 2

Body: Die cast zinc

Bolt: Steel 15/16" projection; 3/4" SFIC

Door thickness: 7/8" to 1 3/8"

Barrel diameter: 1 1/8"

Finishes: Conventional and FSIC formats - 605 and 626; SFIC format - 626 only

Drawer deadbolt locks



CL771G

Cylinder formats:
CL200PB - Conventional format

Interchangeable Core formats:
CL888R - Full Size IC (FSIC)
CL771G - Small Format IC (SFIC)

Rekeying: Release mechanism allows Conventional cylinder replacement. Interchangeable cores replaced using control key

Certifications: ANSI 156.11 - Conventional Grade 1; FSIC and SFIC Grade 2

Body: Die cast zinc

Bolt: Steel 3/4" projection

Door thickness: 7/8" to 1 3/8"

Barrel diameter: 1 1/8"

Finishes: Conventional and FSIC formats - 605 and 626; SFIC format - 626 only

Rim deadbolt lock



CL775G

Interchangeable Core format:
CL775G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc cylinder housing, stamped steel back plate and steel case

Bolt: 1/2" projection

Material thickness: up to 1 1/16"

Barrel diameter: 1 1/8"

Compatibility: Retrofits Best 5L Series

Finish: 626

Rim latch



CL725G

Interchangeable Core format:
CL725G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc cylinder housing, stamped steel back plate and steel case

Material thickness: up to 1 1/16"

Barrel diameter: 1 1/8"

Compatibility: Retrofits Best 5L Series

Finish: 626

Cam locks



CL920R

Interchangeable Core formats:
CL920R - Full Size IC (FSIC)
CL720G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc

Body diameter: 1 1/8"; across flats 7/8"

Mounting cutout: 1 5/32"

Material thickness: .08" to 1 1/8"

Finish: 626

Rachet locks



CL729G

Interchangeable Core formats:
CL929R - Full Size IC (FSIC)
CL729G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc

Body diameter: 1 1/8"

Material thickness: up to 1/4"

Finish: 626

Mailbox lock



CL728G

Interchangeable Core format:
CL728G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc housing; steel body

Barrel length: Adjustable

Handing: RH standard

Retrofits: Best BL

Finish: 626

Keying options

Large format keying:
Conventional and FSIC cylinder formats available in standard pin and tumbler, Primus XP and Primus XP UL 437 high-security mechanisms. Everest 29 S123 keyway standard. Classic and restricted keyways also available.

Small format keying:
SFIC cylinder format available in standard pin and tumbler mechanism (A2 pinning); Everest 29 R keyway.

Available keyed alike (KA), keyed different (KD) and master keyed.

FSIC and SFIC construction cores available.

Finishes

Bright brass 605 | Satin chrome 626