HP3000 Series Tubular Lock with Push/Pull Paddle Trim

Strikes

ANSI Curved Lip
(Standard)
Brass, bronze or stainless steel, 4-7/8" (124mm) x 1-1/4" (57mm) x 1-1/4" (57mm) lip to center.

To order with push/pull paddle trim, see Quick Codes, page 6. To order separately, specify 217L13 x Finish.



Curved Lip Box
(Optional)
Brass, 2-3/4" (70mm) x 1-1/8" (29mm) x 1-1/4" (57mm) lip to center.

To order with push/pull paddle trim, see Quick Codes, page 6. To order separately, specify 586L19 x Finish.



ANSI Wrought Strike Box
To order with push/pull paddle trim, see Quick Codes, page 6.

To order separately, specify 120F76.



Full Lip Strike (SF114)
Brass, 2-1/4" x 1-3/4" x 1-1/4" lip to center. No optional lip lengths.

To order separately specify 680L50M020 x Finish.
Anti-rattle tab.



Full Lip Strike – 1/4" Radius Corners (SFR114)

Brass, 2-1/4" x 1-3/4" x 1-1/4" lip to center. No optional lip lengths.

To order separately specify 680L51M020 x Finish.
Anti-rattle tab.



Kits

Kit for Retrofitting HP3000 Push/Pull Paddle Trim
Use to cover prep from HL10 series push/pull trim and other manufacturer's trim, when retrofitting HP3000 trim. Contains 2 retrofit plates and 8 screws. Available in 630 finish only. To order, specify 791F39.



Positive Pull Stop Kit
Used on openings where weather stripping is installed or when door closers are not utilized, this kit prevents the latch from retracting when pulling door closed Contains 2 wood screws, 2 machine screws and instructions. To order, specify 813F068.



Strikes/Kits

ML2000 and ML20900 Mortise Locks with Push/Pull Paddle Trim (HPSK)

Strikes

ANSI Straight Lip (standard)

Brass, bronze or stainless steel
Non-handed
4-7/8" (124mm) x 1-1/4" (32mm) x 1-1/8" (29mm) lip to center (standard)
Optional lip lengths: 7/8" (22mm), 1" (25mm), , 1-1/8" (29mm), 1-1/4" (32mm), 1-3/8" (35mm), 1-1/2" (38mm), 1-3/4" (44mm), 2" (51mm), 2-1/4" (57mm), 2-1/2" (64mm), 2-3/4" (70mm), 3" (76mm)

ANSI Curved Lip

Brass, bronze or stainless steel
Handed
4-7/8" (124mm) x 1-1/4" (32mm) x 1-1/4" (32mm) lip to center (standard)
Optional lip lengths: 1-1/8" (29mm), 1-3/8" (35mm), 1-1/2" (38mm), 1-3/4" (44mm), 2" (51mm), 2-1/4" (57mm), 2-1/2" (64mm), 2-3/4" (70mm), 3" (76mm)

	Part No.	Description
Note: Only Available with ML2000  Latchbolt x Deadbolt LH Shown	236L72	Straight Lip
	340L60	Curved Lip for RH/LHR
	340L61	Curved Lip for LH/RHR
 Latchbolt Only LH Shown	236L73	Straight Lip
	340L62	Curved Lip for RH/LHR
	340L63	Curved Lip for LH/RHR
 Deadbolt Only	236L74	Straight Lip
 Blank Filler Plate	236L70	Straight Lip

To order strike with lockset, see How to Order, page 15.
To order strike separately, specify Part No. x Lip Length x Finish (e.g., 340L60 x 1-1/2" x 626).

Kits

Positive Pull Stop Kit

Used on openings where weather stripping is installed or when door closers are not utilized, this kit prevents the latch from retracting when pulling door closed. Contains 2 wood screws, 2 machine screws and instructions. To order, specify 813F068.



ANSI Wrought Strike Box

To order with lockset, see Quick Codes, page 15.
To order separately, specify 120F76.



Open Back

Size: 5-1/4" (133mm) x 1/4" (32mm).

Hand	Door Thickness	Part
LHR	1-3/4" (44mm)	411L63 016
	2" (51mm)	411L63 018
	2-1/4" (57mm)	411L63 020
RHR	1-3/4" (44mm)	411L62 016
	2" (51mm)	411L62 018
	2-1/4" (57mm)	411L62 020

To order with lockset, see Quick Codes, page 15. To order separately, specify Part No. x Door Thickness x Finish (e.g., 411L62 x 2" x 626).



Rabbeted Front and Strike

Brass or bronze
For 1/2" (13mm) rabbet
No optional lip lengths

	Part No.	Hand
Latchbolt x Deadbolt	318F66 318F69	RH/LHR LH/RHR
Latchbolt only	318F64 318F67	RH/LHR LH/RHR
Deadbolt only	318F65 318F68	RH/LHR LH/RHR

To order with lockset, see Quick Codes, page 15.
To order separately, specify Part No. x Finish (e.g., 318F66 x 626).

