
AIPHONE®

GT-TLI

Telephone Line Interface for GT Series



DESCRIPTION:

The GT-TLI is a Telephone Line Interface adaptor that connects to a GT Series Tenant Station and provides automatic telephone dialing when that tenant is called. It can also be programmed to directly dial a telephone number when called from the GT Series Entrance Panel, even without a tenant station designated. For applications when the tenant wishes to answer from the hardwired tenant station or from a telephone, or where telephone-only calling is desired (such as a building manager), the GT-TLI provides that functionality. Once communication is established through the phone line, the associated door can be released from the telephone.

FEATURES:

- External telephone number transfer
- Program locally or remotely
- Control GT entry panel door release relay and/or relay on GT-TLI
- Set transfer mode from remote phone
- Enable / Disable call-in from door panel via phone

SPECIFICATIONS:

Power:	12V-24V AC/DC - 0.5A	
Consumption:	12V AC/DC 95mA	24V AC/DC 45mA
Standards:	EN60950 EN55022 Edition 98 Class B EN55024 Edition 98 Class B FCC parts 68 & 15 IC CS-03	
Capacity:	1 call number (16 digits)	
Memory:	Non-volatile	
Temp. rating:	32°F - 140°F, 0°C - 40°C	
Dimensions:	9-7/16” x 7-1/16” x 2-1/16”	
Weight:	6.35 oz.	

Aiphone Corporation
1700 130th AVE NE * Bellevue, WA 98005
Ph: (800) 692-0200 * Fax: (425) 455-0071
tech@aiphone.com