

new

9600 Series

The **stylish windstorm-rated,** surface mounted solution

The 9600 series is a windstorm-rated, surface mounted electric strike designed to accommodate rim exit devices with a 3/4" throw Pullman latchbolt. All components are completely encased within its 3/4" thick stainless steel housing, so no cutting on the frame is required for installation. Simply place the electric strike on the surface of the frame, align it with the exit latchbolt and install. Adjustments have never been easier as the base is now separate from the cover. It is field selectable for fail secure and fail safe operation, and for 12 or 24VDC.

The 9600 is the only surface mounted electric strike designed with the strength and durability required to exceed the severe forces of ANSI Windstorm testing.

Specifications


- ANSI 250.13-2003 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (6th Edition) listed
- ANSI/BHMA, A156.31 Grade 1
- RoHS compliant
- Patent: 6,392,520


Frame Application

- Metal
- Wood

Electrical (continuous duty)

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC
- PoE friendly





Standard Features

- Installs in metal or wood frames
- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Tamper resistant
- Static strength 2,000 lbs.
- Dynamic strength 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail safe/fail secure
- Dual voltage 12 or 24VDC
- Horizontal adjustment
- Non-handed
- Internally mounted solenoid
- Accommodates up to 3/4" Pullman latch
- Five-year limited warranty

** Independently verified by a nationally recognized testing laboratory.*

Optional Features

- **LBM** » Latchbolt monitor
- **LBSM** » Latchbolt strike monitor

Accessories

9400/9500/9600-108 » Spacer plate (black or 630 finish)

SMB » Surface mounting box

2001M » Plug-in bridge rectifier

2004M » ElectroLynx® adapter

2005M3 » SMART Pac® III

2006M » Plug-in buzzer

Finishes

630 » Satin stainless steel

605 » Bright brass

606 » Satin brass

612 » Satin bronze

613 » Bronze toned

613E » Dark Oxidize Satin Bronze *(NEW)*

629 » Bright stainless steel

RIM EXIT DEVICES

FIELD SELECTABLE (12 OR 24VDC)

FIELD SELECTABLE (FAIL SECURE / FAIL SAFE)

GRADE 1

OUTDOOR RATED

UL 1034 BURGLARY LISTED

ANSI A250.13-2003 WINDSTORM RESISTANT

hes®
ASSA ABLOY

© 2015, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company.