7500 Series

The Grade 1, fire-rated pre-load solution



Specifications

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL 1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- MEA New York City accepted
- UBC-7-2-94, Uniform Building Code
- Patent #5,484,180

Standard Features

- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail safe/fail secure
- Accommodates pre-load (fail secure only)
- Non-handed
- Internally mounted solenoid
- Strike body depth 1-11/16"
- Plug-in connector
- Trim enhancer
- Five year limited warranty

Optional Features

- LBM - Latchbolt monitor

Electrical

- .45 Amps @ 12VDC continuous duty
- .25 Amps @ 24VDC continuous duty

Finishes

- 630 - Satin stainless steel
- 605 - Bright brass
- 606 - Satin brass
- 612 - Satin bronze
- 613 - Bronze toned
- 629 - Bright stainless steel

Frame Application

- Metal
- Wood

Copyright © 2011, HES, Inc.

ASSA ABLOY, the global leader in door opening solutions