8000 Series

The concealed no cut solution for cylindrical locksets



Specifications

UL 1034, burglary-resistant listed •
ANSI/BHMA A156.31, Grade 1 •
Patent #5,934,720 and patent pending •

Standard Features

No cutting on frame required •
Vertical adjustability to accommodate door sag and misalignment •
Tamper resistant •
Static strength 1,500 lbs. •
Dynamic strength 70 ft-lbs. •
Endurance 500,000 cycles •
Field selectable fail safe/fail secure •
Dual voltage 12 or 24 VDC/VAC •
Non-handed •
Internally mounted solenoid •
Accommodates 1/2" - 5/8" cylindrical latchbolt •
(5/8" with 1/8" door gap)
Strike body depth 1-1/16" •
NEW! Strike body width decreased to 1-7/16" •
to increase frame compatibility
Five year limited warranty •

Optional Features

LBM - Latchbolt monitor •

Electrical

.24 Amps @ 12VDC/VAC •
.12 Amps @ 24VDC/VAC •
DC continuous duty/AC intermittent duty only •

Finishes

630 - Satin stainless steel •
605 - Bright brass •
606 - Satin brass •
612 - Satin bronze •
613 - Bronze toned •
629 - Bright stainless steel •
BLK - Black •

Frame Application

Metal •
Wood •

Copyright © 2011, HES, Inc.

ASSA ABLOY, the global leader in door opening solutions