

8000

Series

The concealed no cut solution
for cylindrical locksets

hes
ASSA ABLOY



Specifications

- UL 1034, burglary-resistant listed •
- ANSI/BHMA A156.31, Grade 1 •
- Patent #5,934,720 and patent pending •

Standard Features

- No cutting on frame required •
- Vertical adjustability to accommodate door sag and misalignment •
- Tamper resistant •
- Static strength 1,500 lbs. •
- Dynamic strength 70 ft-lbs. •
- Endurance 500,000 cycles •
- Field selectable fail safe/fail secure •
- Dual voltage 12 or 24 VDC/VAC •
- Non-handed •
- Internally mounted solenoid •
- Accommodates 1/2" - 5/8" cylindrical latchbolt •
(5/8" with 1/8" door gap)
- Strike body depth 1-1/16" •
- NEW! Strike body width decreased to 1-7/16" •
to increase frame compatibility
- Five year limited warranty •

Optional Features

- LBM - Latchbolt monitor •

Electrical

- .24 Amps @ 12VDC/VAC •
- .12 Amps @ 24VDC/VAC •
- DC continuous duty/AC intermittent duty only •

Finishes

- 630 - Satin stainless steel •
- 605 - Bright brass •
- 606 - Satin brass •
- 612 - Satin bronze •
- 613 - Bronze toned •
- 629 - Bright stainless steel •
- BLK - Black •

Frame Application

- Metal •
- Wood •