



9400 Series
Slim-line
Works with rim exit devices with a 1/2" throw latchbolt

9500 Series
Fire-Rated
Works with rim exit devices with a 3/4" throw latchbolt

9600 Series
Windstorm-Rated
Works with rim exit devices with a 3/4" throw latchbolt

9700 Series
Fire-Rated & Windstorm-Rated
Works with Corbin Russwin SecureBolt™ and Yale SquareBolt® exit devices



9000 Family

Surface Mounted Electric Strikes

Sophistication
Stylish Looks

Designed with a stainless steel decorative cover
Available in six finishes to match any decor
Sleek lines complement ASSA ABLOY exit devices

Convenience
Easy Installation

Completely surface mounted for quick installation
Base and cover are separate for easy adjustments
Field selectable fail safe/fail secure

Quality
Above and Beyond

Exceeds Grade 1 standards for strength and performance
Components encased in 1/2" stainless steel housing
Independently verified above and beyond testing

ASSA ABLOY, the global leader in door opening solutions

hesinnovations.com

Series Options, Accessories & Specifications

Optional Features

LBM » Latchbolt monitor

LBSM » Latchbolt
strike monitor

Accessories

9400/9500/9600/9700-

108 » Spacer plate
(black or 630 finish)

9000-MTK » Metal
template kit

SMB » Surface
mounting box

2001M » Plug-in
bridge rectifier

2004M » ElectroLynx
adapter

2005M3 » SMART Pac® III

2006M » Plug-in buzzer

Frame Application

- Metal

- Wood

Finishes

630 » Satin stainless steel

605 » Bright brass

606 » Satin brass

612 » Satin bronze

613 » Bronze toned

613E » Dark oxidized
satin bronze (NEW)

629 » Bright stainless steel

Electrical

(continuous duty)

- .45 Amps @ 12 VDC

- .26 Amps @ 24VDC



9400 Series

The Easy-Install, Slim-Line, Surface Mounted Solution

Standard Features

- Decorative cover for a sleek look
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

Listings and Patents

- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- RoHS compliant
- Patents: 6,392,520 and 8,454,520

The 9400 Series works with rim exit devices with a 1/2" throw latchbolt



9500 Series

The Strong & Durable, Fire-Rated, Surface Mounted Solution

Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- UL 1034, burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- California Fire Marshall listed
- NFPA 80-07 compliant
- RoHS compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520

The 9500 Series works with rim exit devices with a 3/4" throw latchbolt



9600 Series

The Stylish, Windstorm-Rated, Surface Mounted Solution

Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

Listings and Patents

- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,392,520 and 8,454,520

The 9600 Series works with rim exit devices with a 3/4" throw latchbolt

new



9700 Series

Surface Mounted Electric Strike

Works with Corbin Russwin SecureBolt™ and Yale SquareBolt® exit devices

Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)

- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520

The Stylish,
Windstorm-
Rated and
Fire-Rated,
Square Bolt
Solution



Yale SquareBolt® Exit Device

hesinnovations.com

For information call 800.626.7590 or visit us online at www.hesinnovations.com

HES-056-0915