

DESCRIPTION:

The IS-SS-RA is a stainless steel flush mount audio door station with an emergency call button. The unit is equipped with ADA compliant lettering and Braille signage. A call status indicator is included to meet ADA assistance requirements.


The emergency button will trigger two selectable relay outputs for activation of external systems or devices.

The unit is equipped with a CCTV camera input (Analog NTSC 1Vpp) for integration of a separate camera for viewing the area where the unit is located. The camera will come on when a call is placed from the unit, or when called by the master station. The unit is made of stainless steel and includes tamper resistant screws.

The IS-SS-RA is compatible with the IS series communication system. Wiring is CAT-5e or CAT-6 to the designated exchange unit (IS-CCU, IS-SCU).

FEATURES:

- Audio communication between master station and calling area
- CCTV input for integration of video camera
- Emergency call button
- Two selectable relay outputs
- ADA compliant lettering and Braille signage
- LED call status indicator
- Stainless Steel faceplate with tamper resistant screws



IS-SS-RA

Stainless Steel Flush Mount Audio Door Station with Emergency Call Button

FEATURE CALL-OUT DEFINITIONS:

- [1] Microphone
- [2] Speaker
- [3] Directory card
- [4] Call status indicator
- [5] Call button
- [6] Emergency signage with Braille

SPECIFICATIONS:

- Power Source: 48VDC (supplied from CEU)
- Communication: Open voice hands-free
- Wiring: CAT-5e or CAT-6
- Wiring distance: 980'
- Camera Input: Analog NTSC 1Vpp
- Door release: 24V AC/DC, 500mA (N/O, COM, N/C)
- Operation Temp: 14° - 140°F (-10° - 60°C)
- Dimensions: 7" W x 11-3/4" H x 1-7/8" D

FEATURE CALL-OUTS:

