
AIPHONE®

JP-8Z

Distribution Adaptor



DESCRIPTION:

The JP-8Z is a distribution adaptor for the JP Series. The adaptor is utilized when homerun wiring is desired. The JP-4MED master station and each JP-4HD sub master station will connect to this adaptor using CAT-5e/CAT-6 cable. The JP-8Z can surface mount using the mounting holes or with the W-DIN11 mounting rail. One or two PS-2420UL power supplies are used, depending on how many sub master stations are connected.

JP-8Z FEATURES:

- Homerun up to 7 sub monitors
- 165’ wiring distance to each JP-4HD
- Compatible with JP Series and JM Series

SPECIFICATIONS:

Power Source:	24V DC - use PS-2420UL (1 per 4 JP-4HD)
Wire Type:	CAT-5e / CAT-6 for stations 18AWG 2 conductor for power
Mounting:	Surface wall mount or DIN rail (W-DIN11)
Temperature:	32-104°F (0-40°C)
Dimensions:	4-5/16” H x 4-7/8” W x 2-7/16” D
Weight:	Approx. 0.46 lbs (210g)

Aiphone Corporation
1700 130th AVE NE * Bellevue, WA 98005
Ph: (800) 692-0200 * Fax: (425) 455-0071
tech@aiphone.com